



EAO AG

Tannwaldstrasse 88

4600 Olten

Switzerland

Phone: +41 62 286 9111

info@eao.com

Part No. 45-1231.11G6.000.101, Illuminated Pushbutton



[Specifications](#) | [Bill of Materials](#)

Specifications

| | |
|-------------------------------------|-------------------------------|
| Actuator | <u>Illuminated pushbutton</u> |
| Lens Colour | Yellow, transparent |
| Function | 2 Positions, momentary (O<I) |
| Housing Material | Plastic |
| Shape of Handle or Frontring | raised/ level to bezel |
| Lock System | None |
| Key | None |
| Key Type | None |
| Switching Angle | None |
| Contacts | 1NO |
| Terminal | Screw terminal |
| Voltage Illumination | 24V AC/DC |

| | |
|--|--|
| Mounting Type | Front mounting |
| Mounting Style | Holder |
| Environmental Rating | IP66, IP67, IP69K |
| Industry Standards/Certifications | UL, CSA, VDE, CCC, CE, RoHS |
| Switching Function | On-Off |
| Illumination | Yellow |
| Contact Material | Silver |
| Termination Style | Screw |
| Mechanical Life | Maintain 500'000 switching cycles Momentary 3'000'000 switching cycles |
| AC Voltage | 500 V |
| DC Voltage | 500 V |
| Switching Current | 10 A |

Bill of Materials

| | |
|-------------------------|------------------|
| Actuator | 45-2231.11G0.000 |
| Holder | 45-2300.1000.000 |
| Switch Element 1 | 45-311.1Z10 |
| LED Module | 45-320.1G16 |