

[Go](#)[Register // Login](#)[My Parts \(0 items \)](#)[Contact Molex](#) | [Find Distributor](#)[Connectors](#)[Sockets /
Edge Cards](#)[Cable
Assemblies](#)[Antennas /
Wireless](#)[Optical
Solutions](#)[Printed Circuit
Products](#)[Automation /
Industrial](#)[Lighting
Products](#)Home: [PCB Headers](#)**Part Number: 47261-0001****4.00mm Pitch Po-Go Pin Connector, Surface Mount, Vertical, 2 Circuits, Lead-Free**[Series image - Reference only](#)**Status:** **OBSOLETE**
Replacement: [Contact Molex](#)**Series:****Category:** [47261](#)
[PCB Headers](#)**Overview:** [Pogo Pins](#)
[Go to **Part Detail**](#)[CHECK DISTRIBUTOR INVENTORY](#)[Add to My Parts](#)[Email this page](#)**Specifications & Other Documents:**Note - Please disable browser pop-up blockers to view documents on [www.molex.com](#)Questions on Product Environmental Compliance? Email productcompliance@molex.com[EU RoHS](#) : RoHS Compliant by Exemption[China RoHS](#) : [REACH SVHC](#) : Not Reviewed[Low-Halogen Status](#) : Not Reviewed[RoHS Certificate of Compliance \(PDF\)](#)[Multiple Part Product Compliance Form](#)**Application Tooling** ♦♦[FAQ](#)

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

Previously Available Application Tooling[Check our list of old tooling that used to be available for this part](#)**Part Detail**[SHOW ALL](#)**General**

Status	Obsolete
Category	PCB Headers
Series	47261
Application	Board-to-Board, Signal
Comments	Action Height: 7.90mm
Overview	Pogo Pins
Product Name	PoGo Pin
UPC	822350150965

Physical

Breakaway	Yes
Circuits (Loaded)	2
Circuits (maximum)	2
Durability (mating cycles max)	10,000
First Mate / Last Break	No
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	None
Mated Height	7.90mm
Material - Plating Mating	Gold

Material - Plating Termination	Gold
Net Weight	291.154/mg
Number of Rows	1
Orientation	Vertical
PCB Locator	No
PCB Retention	Yes
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface	4.00mm
Plating min - Mating	0.406 μ m
Polarized to Mating Part	No
Polarized to PCB	No
Shrouded	No
Stackable	No
Temperature Range - Operating	-40 $^{\circ}$ C to +85 $^{\circ}$ C
Termination Interface: Style	Surface Mount

Electrical

(Please review the Product Specification for specific details.)

Current - Maximum per Contact	2A
Voltage - Maximum	12V DC

Solder Process Data

Lead-free Process Capability	Reflow Capable (SMT only)
Process Temperature max. C	250

Material Info

Molex Connectors

- Wire-to-Board
- Board-to-Board
- Wire-to-Wire
- Input/Output (IO)
- FFC/FPC
- Sockets

Other Products

- Fiber Optic Products
- Antennas
- Industrial Automation
- Membrane Switches
- Copper Flex
- PCB Assemblies
- Woodhead Electrical
- Solid State Lighting
- Application Tooling

Resources

- Contact Us
- Catalog
- Cross-Reference
- Industries
- Literature
- Product Name

Company Info

- About Us
- Careers
- ecocare
- Investors
- Press Room
- Shows & Events
- Supplier Portal

Other Info

- Feedback
- Help
- Legal Disclaimer
- Trademarks
- View Mobile Site
- Privacy Policy
- Sitemap

Stay Connected with Molex:

□□□