Honeyw	ell			→ Honeywe	Il.com → Automation & C	ontrol Solution
HOME	ABOUT US	KEY INDUSTRIES SERVED	PRODUCTS & INFORMATION	NEWS & EVENTS	SALES & SUPPORT	LOGIN
loneywell Se	nsing and	Control				LE
Search	Э	4TL153-1 (Home: Products: Switches »	MICRO SWITCH™ Toggle Switches » TL)			contacts
narrow your searc Products Controls Monitorin Lighting (352) Machine Safety (17 Sensors (6224) Switches (9749) Wireless (39)	g and	TL Series Standard	Toggle Switch, 4 pole, 3 position, Screw termi Lever	nal,	Customer Servic Technical Suppo Global Sales & S View Site Demo Site Comments?	rt
Control and Instrumentation (10 Electromechanical Magnetic (541) Optical/Infrared (10 Thick Film (1764)	(9301)	Actual product appearance may vary.	Sales & Service 🥥	Distributor Inventory 🥹	VIDEO - Dr. Larry Goldstein explains our newest and bes technologies. Meet Dr. Larry	0
More						my links
Overview Specs Documentation Application Notes ew products Product Specifications New Wireless Products				Login to iCOM Login to Rep/AD Login to Digital L		
o farther. Work smarte ssibilities. Just by cutt d making the switch.		Circuitry/Operating action	Keyway Center Key	oosite way ition		News Cente
reless Web Site GLA and WPMM Resource	d out more		$\begin{array}{c} & & & & \\ 3 & 2 & 1 & 3 & 2 & 1 & 3 \\ & & & & & \\ 6 & 5 & 4 & 6 & 5 & 4 & 6 \\ & & & & & & \\ 9 & 8 & 7 & 9 & 8 & 7 & 9 \end{array}$	2 1 5 4 8 7	HONEYWELL AI ADDITION TO R RESIDENTIAL D INTERLOCK SW FEATURE RUG HOUSING HONEYWELL R UNLIMITED POT NEW LIMITLES SWITCHES HONEYWELL'S	ELIALIGN™ OOR (ITCHES THAT GED, PLASTIC ELEASES TENTIAL WITH S™ WIRELESS XYR6000
hite papers Wireless Switches C	Offer			11 10 DN	WIRELESS POS ENABLES MONI HAZARDOUS AI REMOTE LOCA	TORING IN REAS AND
Unlimited Benefit Basic Switches Are I Equal		Product Type Ampere/Voltage Range (Resistive Load)	MICRO SWITCH™ Toggle Switch 0.75 A at 115 Vdc,0.5 A to 20 A at 0.5 Vdc to 2 at 0.5 Vac to 277 Vac		A	
Applying Precision S Sensors for Medical	Devices	(Resistive Load) Circuitry Action	4PDT 3 position		А	nniversary sit
New Ways to Measu Choosing Safety Sw		Mounting	Bushing 15/32 in			
Specifying Hour Met	ters	Termination Lever Type UL/CSA	Screw Standard L191: 15 A-125, 250, 277 Vac; 1/2 Hp-125 Vac	; 1 Hp-250, 277 Vac; 5 A-120 Vac "	L'	
Need help?		Comment	Grounded lever			
Click here to c	contact us	Availability UNSPSC Code UNSPSC Commodity	Global 30211908 30211908 Toggle switches			

Terms & Conditions | Privacy Statement | Site Map