


Isolating plugs - ST-K 4 - 5025462

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Isolating connector, can be used in UK...-TG, UKK...-TG, UDK...-TG, MBK...-TG, DIK...-TG, DOK...-TG, and ZFK...-TG disconnect terminal blocks, color: gray

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 095321
Weight per Piece (excluding packing)	1.74 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Color	gray
Insulating material	PA
Flammability rating according to UL 94	V2

Dimensions

Width	4.5 mm
Length	10 mm
Height	31.2 mm

General

Nominal current I_N	16 A
Nominal voltage U_N	400 V

Connection data

Connection method	Plug connection
-------------------	-----------------

Standards and Regulations

Isolating plugs - ST-K 4 - 5025462

Technical data

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141140

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002497
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approvals submitted

Isolating plugs - ST-K 4 - 5025462

Approvals

Approval details

EAC

EAC
