

Global - English


[Web Site](#)
[Optoelectronics Stock Check](#)

---


[Products](#)
[Applications](#)
[Documentation](#)
[About Us](#)
[Where to Buy](#)
[Investor Relations](#)
[News & Events](#)
[Contact Us](#)

[Request more info](#)

**Part Number : 5151138F**



- [UL File Card – PCFR2AD](#)
- [Lightpipe Selector Guide \(Interactive\)](#)
- [5151138 Detailed Spec](#)



This is a  
RoHS Compliant Product  
[To learn more click here](#)

### General Description

Series	515
Configuration	3 Array Rectangular Lightpipe
Description	3 ARRAY .075"X .122" VERTICAL RECTANGULAR WITH HORIZONTAL PITCH .250" X .075" HIGHX.69" LONG, INPUT .225" LEFT SIDE,130" REMAINING
Package Options	Bulk Packaging
Sizes	1.9 X 3.1mm
Shape	VERTICAL RECTANGLE
Viewing	Right Angle
Mounting Method	LOW PROFILE PCB MOUNTABLE
Mounting Hole Size	.060" +/- .002
Mounting Hole Pitch	.170

### Absolute Maximum Ratings (Ta = 25°)

Operating Temperature	-30 to +100
Storage Temperature	-30 to +100

### Operating Characteristics

Pitch Between	.250
---------------	------

[EAX Login](#) 
[Site Map](#)
[Privacy and Cookies Policy](#)
[Terms and Conditions](#)
[Dialight BTI](#)
[Alert Services](#)

Copyright © 2013, Dialight. All Rights Reserved.