


| | | |
|-------------------|----------------------------|------------------------------------------------------------------------------------|
| U.I. Lapp GmbH | PRODUCT INFORMATION |  |
| | SKINDICHT® SM-M | 29.11.2013 |



Good chemical resistance



Mechanical resistance

Application range

Used when a gland has to be countered, or in through-holes on thin-walled housings

Design

Metric connection thread acc. to EN 50262

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Material: Nickel-plated brass

| | | |
|--------------------|------------------------------|-------|
| Product Management | Document: LAPP_PRO1025EN.pdf | 1 / 2 |
|--------------------|------------------------------|-------|



SKINDICHT® SM-M

29.11.2013

| Part number | Article designation / size | Thickness (mm) | SW (mm) | Outer Ø (mm) |
|-----------------|----------------------------|----------------|---------|--------------|
| SKINDICHT® SM-M | | | | |
| 52103000 | 12 x 1,5 | 3.0 | 15 | 16,5 |
| 52103010 | 16 x 1,5 | 3.0 | 19 | 20,9 |
| 52103020 | 20 x 1,5 | 3,5 | 24 | 26,4 |
| 52103030 | 25 x 1,5 | 4.0 | 30 | 33.0 |
| 52103040 | 32 x 1,5 | 4.0 | 36 | 39,6 |
| 52103050 | 40 x 1,5 | 5.0 | 46 | 50,6 |
| 52103060 | 50 x 1,5 | 5.0 | 60 | 66.0 |
| 52103070 | 63 x 1,5 | 5.0 | 70 | 77.0 |
| 52103071 | 75 x 1,5 | 8.0 | 85 | 95.0 |
| 52103072 | 90 x 2 | 10.0 | 102 | 114.0 |
| 52103073 | 110 x 2 | 12.0 | 124 | 135.0 |