



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

Circuit Board Indicators - Through Hole Indicators	
P/N# 5219271F	5 mm Lens Single Color
Description	Discrete LED Lamp
Package Options	100 pieces per bag
Product Type	Through Hole Indicators
Sub Product Type	Discrete LED
Configuration	5 mm Lens
Lamp Type	Single Color
Lens Color	Diffused
Viewing Angle	50 degrees
Test Current (mA)	10mA

Absolute Maximum Ratings (Ta = 25 °)	
Reverse Current	10 @ Vr = 12V
Forward Current Continuous	40 mA
Forward Current Pulse	500 mA
Derating	from 46Å° @ .74mA/Å°C
Reverse Voltage	12 V
Solder Temp	230Å° for 7 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C
Peak Wave Length	586

Distributor Stock Check

Check stock with our distributors now.

5219271F

[check stock](#)

how to purchase


- [sales contacts](#)
- [stock check](#)

search

[Product Line Search](#)

Please select a Product Line to search.

[find](#)



Operating Characteristics

LED Position	
Color	Yellow
Lamp Type	Single Color
LED Type	GaAsP
Intensity Min (mcd)	4.5
Intensity Typ (mcd)	
Intensity Max (mcd)	28.0
Fwd Voltage Min	
Fwd Voltage Typ	2.0
Fwd Voltage Max	2.5
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	587
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	130
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Part # / Text Search

Part No.:

Text Search:

[search](#)

- [quick links](#)
- [Dialight Corporate Video](#)
 - [Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File](#)
 - [Application Notes](#)
 - [FAQs](#)
 - [Dialight Ltd \(UK\)](#)
 - [Dialight Garufo](#)
 - [Dialight BLP](#)
 - [LumiDrives](#)