



Actual



Family

Catalog Number: 5233-PT
Product ID: 7TAD012100R0033
UPC Number: 78620967408
Status: Active

3/4 Inch Straight Zinc Plated Steel Liquidtight Push-in Connector, Non-insulated

- High performance and pull-out strength
- Installs up to 3 times faster
- No disassembly required

North American Specifications (UNSPSC)

| | |
|------------------|--|
| UNSPSC | 39121420 Liquid tight connectors |
| IGCC | 4585 Liquid tight connectors |
| Brand Name | T&B |
| Type | Connectors-Straight |
| Special Features | Innovative Labor-Saving Design, Simple Push-In Connection |
| Application | For Liquid and Dust-Tight Connections Between Flexible Jacketed Metallic Conduit and a Box or an Enclosure |
| Standard | UL E23018, CSA |
| Size | 3/4 Inch |
| Material | Steel |
| Finish | Zinc Plating |

European Specifications (ETIM)

| | |
|---|--|
| ETIM | EC001180 Screw connection for protective metallic hose |
| Nominal size in inch | 3/4 inch |
| Model | Straight |
| Revolving thread | N |
| Construction type | External thread |
| Connection type screw connection to housing | Plug-in connection |
| Thread type | NPT |
| Thread connection size | Other |
| One-piece | Y |
| Material housing | Steel |
| Surface protection | Zinc coated |
| Operating temperature | 0-+105°C |

Packaging

| | |
|---------------------------|-----------------|
| Inner Quantity | 25 |
| Inner Dimensions (inches) | 8x5x4 |
| Outer Quantity | 50 |
| Outer Dimensions (inches) | 8.49x5.19x8.13 |
| Weight Uom | 23 lbs. per 100 |

Documents / Support Tools

| | |
|-----------------------------|----------------------|
| Technical Data Sheet US | wsd-001160 |
| Technical Data Sheet CA | Available on Website |
| Technical Data Sheet Global | tds000121 |
| Instruction Sheet 1 | ta04752-tb2 |
| Catalog US 1 | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com