



Actual

**Catalog Number:** 5241-PT  
**Product ID:** 7TAD012100R0035  
**UPC Number:** 78620967413  
**Status:** Active

3/8 Inch 45 Degree Malleable Iron Liquidtight Push-in Connector, Non-insulated

- High performance and pull-out strength
- Installs up to 3 times faster
- No disassembly required

### North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B
Type	Connectors-45 Degree
Special Features	Innovative Labor-Saving Design, Simple Push-In Connection
Application	For Liquid and Dust-Tight Connections Between Flexible Jacketed Metallic Conduit and a Box or an Enclosure
Standard	UL E23018, CSA
Size	3/8 Inch
Material	Malleable Iron

### European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	3/8 inch
Model	45°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Plug-in connection
Thread type	NPT
Thread connection size	Other
One-piece	Y
Material housing	Other
Operating temperature	0-+105°C

### Packaging

Inner Quantity	25
Inner Dimensions (inches)	6x4.5x4
Outer Quantity	50
Outer Dimensions (inches)	8.68x4.81x6.31
Weight Uom	17 lbs. per 100

### Documents / Support Tools

Technical Data Sheet US	wsd-001160
Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	tds000121
Instruction Sheet 1	ta04752-tb2
Catalog US 1	Available on Website

**For further technical assistance, please contact us...**

Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

8155 T&B Blvd.  
Memphis, TN 38125

Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)