



## Liquidtight Flexible Metal Conduit Fittings

### T&B Catalog Number:

**UPC Number:** 5250  
78621005250  
**Status:** Active  
**Description:**

4 Inch 45 degree malleable iron liquidtight connector, non-insulated

#### Features

Ability to install quickly with low torque effort

#### Application

Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

#### General

Style	Non-Insulated
Trade Size (inches)	4
Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

#### Dimension Information

Dimension A (inches)	5 1/2
Dimension B (inches)	4 5/8
Dimension C (inches)	1 1/8

#### Specifications

3dmodel	Available on Website
---------	----------------------

#### Accessories & Components

Wiremesh Grips for Liquidtight Fittings	WMG-LT10
---	----------

#### Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	1200 lbs. per 100

#### Certifications

RoHS Compliance	Yes
-----------------	-----

#### Certifications



File Nbr:  
E 23018

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com