


52® /53® Series Liquidtight Fittings and Flexible Metallic Conduits

Nylon-Insulated CHASE® Connectors




Steel or malleable iron with O-Ring Seal

CAT. NO.	CONDUIT SIZE	DIMENSIONS (IN.)		
		A	B	C
5361†	3/8"	1 1/32	1 3/8	1/8
5362†	1/2"	1 3/8	1 3/8	3/16
5363†	3/4"	1 11/16	1 3/8	1/4
5364†	1"	2 1/32	2 1/16	1/4
5365†	1 1/4"	2 3/8	2 3/8	5/16
5366†	1 1/2"	2 15/16	2 3/4	3/8
5367†	2"	3 9/16	3	3/8
5368†	2 1/2"	4 3/8	3 15/16	7/16
5369†	3"	5 1/8	4 3/8	1/2
5370†	4"	5 3/8	4 3/8	1/2

With SAFE-EDGE® ground cone and double bevel sealing ring (through 2").

† UL listed as grounding means under NEC 351-7.

Nylon-Insulated 90° Angle CHASE® Connectors



Malleable iron


CAT. NO.	CONDUIT SIZE	DIMENSIONS (IN.)		
		A	B	C
5371†	3/8"	1 1/32	1 1/2	3/16
5372†	1/2"	1 13/64	1 15/32	3/16
5373†	3/4"	1 31/64	1 3/8	9/32
5374†	1"	1 23/32	2 1/4	1 1/32

With SAFE-EDGE® ground cone and double bevel sealing ring.

Note: UL Listed Liquidtight; & CSA certified watertight. Suitable for hazardous locations use in Class I, Div. 2; Class II, Div. 1 and 2; Class III, Div. 1 and 2, where general purpose equipment is specifically permitted per NEC® Section 500-2(a).

† UL listed as grounding means under NEC 351-7.

Standard Liquidtight Female Hub Adapter



CAT. NO.	CONDUIT SIZE	DIMENSIONS (IN.)	
		A	B
5271†	3/8"	1 1/32	1 1/16
5272†	1/2"	1 3/8	1 11/16
5273†	3/4"	1 21/32	1 3/4
5274†	1"	1 7/8	2 1/8
5275†	1 1/4"	2 27/32	2 1/2
5276†	1 1/2"	2 3/4	2 11/16
5277†	2"	3 15/32	3 1/16

† UL Listed as grounding means under NEC 351-7.

Prevents severe conduit bends and pullout!

Wiremesh Grips for Liquidtight Fittings



CAT. NO.	CONDUIT SIZE	LIQUIDTIGHT CONNECTORS					
		STRAIGHT	45°	90°	CHASE	90° CHASE	ADAPTER
WMG-LT1	3/8"	5331	5341	5351	5361	5371	5271
WMG-LT2	1/2"	5332	5342	5352	5362	5372	5272
WMG-LT3	3/4"	5333	5343	5353	5363	5373	5273
WMG-LT4	1"	5334	5344	5354	5364	5374	5274
WMG-LT5	1 1/4"	5335	5345	5355	5365	—	5275
WMG-LT6	1 1/2"	5336	5346	5356	5366	—	5276
WMG-LT7	2"	5337	5347	5357	5367	—	5277
WMG-LT8	2 1/2"	5338	5348	5358	5368	—	5278
WMG-LT9	3"	5339	5349	5359	5369	—	5279
WMG-LT10	4"	5340	5350	5360	5370	—	5282

Order wiremesh grip separately: no need to duplicate inventory.

UL File No. E23018

CSA File No. 2884 & 4484