








Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Accessories and Spare Parts

Selection and ordering data

















Version	Suitable for	Lamp voltage	Color	Order no.	List Price \$
	Flush actuator button For flush type, non-illuminated pushbuttons		black	52RA1A1	1.60
			red	52RA1A2	1.60
			green	52RA1A3	1.60
			yellow	52RA1A4	1.60
			blue	52RA1A5	1.60
			gray	52RA1A6	1.60
			orange	52RA1A8	1.60
			kit- all colors	52RA1AN	11.20
				Extended actuator button For extended type, non-illuminated pushbuttons	
red	52RA1B2	1.60			
green	52RA1B3	1.60			
yellow	52RA1B4	1.60			
blue	52RA1B5	1.60			
gray	52RA1B6	1.60			
orange	52RA1B8	1.60			
1 of each color cap	52RA1BN	11.20			
	Mushroom head - Plastic For small 1 5/8"(41.3mm) type, non-illuminated mushroom pushbuttons and push-pull; set screw				
			red	52RB3D2	8.20
			green	52RB3D3	8.20
			yellow	52RB3D4	8.20
			blue	52RB3D5	8.20
			gray	52RB3D6	8.20
			orange	52RB3D8	8.20
			1 of each color cap	52RB3DN	65.60
				Mushroom head - Metal For small 1 5/8"(41.3mm) type, non-illuminated push-pull; set screw	
red	52RB3F2	17.80			
green	52RB3F3	17.80			
	Mushroom head - Plastic For large 2 1/2"(63.5mm) type, non-illuminated mushroom pushbuttons and push-pull; set screw		black	52RB3E1	16.40
			red	52RB3E2	16.40
			green	52RB3E3	16.40
			yellow	52RB3E4	16.40
			blue	52RB3E5	16.40
			gray	52RB3E6	16.40
			orange	52RB3E8	16.40
			1 kit of each color cap	52RB3EN	131.00
				Illuminated mushroom head Illuminated metal	
green	52RB3H3	18.00			
amber	52RB3H9	18.00			
Illuminated plastic		green		52RB3JG	18.00
		red		52RB3JR	18.00
		amber		52RB3JA	18.00
	Replacement Lens for Pilot Lights Plastic lens		red	52RA4P2	5.80
			green	52RA4P3	5.80
			blue	52RA4P5	5.80
			amber	52RA4P9	5.80
			clear	52RA4PA	5.80
			white	52RA4PB	5.80
	Glass lens		red	52RA4G2	22.50
			green	52RA4G3	22.50
			blue	52RA4G5	22.50
			amber	52RA4G9	22.50
			clear	52RA4GA	22.50
			white	52RA4GB	22.50
	Replacement Lens for Push to test/Illuminated pushbuttons Plastic lens		red	52RA5P2	5.80
			green	52RA5P3	5.80
			blue	52RA5P5	5.80
			amber	52RA5P9	5.80
			clear	52RA5PA	5.80
			white	52RA5PB	5.80

Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Accessories and Spare Parts

Selection and ordering data

Version	Suitable for	Lamp voltage	Color	Order no.	List Price	
					\$	
	Replacement lens kit for illuminated selector switches Knob & Insert		red	52RA6P2	5.80	
			green	52RA6P3	5.80	
			blue	52RA6P5	5.80	
			amber	52RA6P9	5.80	
			clear	52RA6PA	5.80	
			white	52RA6PB	5.80	
	Lever inserts Short lever Long lever		red	52RA2A2	0.40	
			green	52RA2A3	0.40	
			blue	52RA2A5	0.40	
			yellow	52RA2A4	0.40	
			gray	52RA2A6	0.40	
			orange	52RA2A8	0.40	
			white	52RA2AB	0.40	
			red	52RA2B2	0.40	
			green	52RA2B3	0.40	
			blue	52RA2B5	0.40	
			yellow	52RA2B4	0.40	
			gray	52RA2B6	0.40	
			orange	52RA2B8	0.40	
			white	52RA2BB	0.40	
	Replacement lens for compact style pilot lights Replacement lenses		red	52RA7P2	5.80	
			green	52RA7P3	5.80	
			blue	52RA7P5	5.80	
			amber	52RA7P9	5.80	
			clear	52RA7PA	5.80	
			white	52RA7PB	5.80	
	① Clear protective boot Offers protection from ice and foreign substances from interfering with button operation	Flush pushbutton operators		52AABA	16.40	
		② Pushbutton guard Prevents accidental operation of the pushbutton	Non-Illuminated pushbuttons Black Max styles, non-Illuminated push-buttons		52AAGP 52AXGP	8.20 8.20
		Lens guard Push to test buttons and pilot lights			52AAGL	8.20
			Black Max styles, push to test buttons and pilot lights		52AXGL	8.20
		③ Guard for mushroom head Additional hole spacing is required on adjacent devices	1 5/8"(41.3mm) mushroom head pushbutton and push-pull operators		52AAGM	33.00
			Black Max styles, 1 5/8"(41.3mm) mushroom head pushbutton and push-pull operators		52AXGM	33.00
		④ Pushbutton locknut Replacement front ring	Pushbutton and push-to-test device		52AANP	2.70
			Black Max styles		52AXNP	2.70
		⑤ Push-pull/pilot light locknut Replacement front ring	Mushroom head and pilot light indicators		52AANL	2.70
			Black Max styles		52AXNL	2.70
		⑥ Selector switch locknut Replacement front ring	Selector switch		52AANS	2.70
Black Max styles, selector switch				52AXNS	2.70	
	Padlock attachments	Flush pushbutton operators		52AALA	24.50	
		Extended operators ¹⁾		52AALB	24.50	
				52AALS	49.00	
	⑦ Padlock cover Can be used to lock devices in the off position	Pushbuttons, selector switches, and non-illuminated mushroom heads		52AALE	47.00	
		Pushbuttons, selector switches, and illuminated mushroom heads				
	⑧ Lock nut wrench	All devices		52MAWB	24.50	
	⑨ Hole plugs	Corrosion resistant		52AAH6	8.20	
		Steel, gray		52ABH6	8.20	
	Spare keys	Stainless steel		52ABHS	24.50	
		501CH (1 key)		D28671015	5.60	
	Grounding kit	All devices		52AL109145	4.20	
	⑩ Touchsafe shield	Illuminated devices (Current revisions only)		52AASH	2.40	
	⑪ Black boot	Extended or flush pushbuttons		52AAB1	16.40	
	⑫ Rubber gasket (5)	All devices		52AAD	2.40	
	⑬ Yellow 90 mm ESTOP ring	All E-Stops		52AAR	4.50	


1) Must be used with step raised cap- 52PA8C2.

Pushbutton Units and Indicator Lights

30 mm Heavy Duty, Watertight/Oiltight, Class 52

Accessories and Spare Parts

Selection and ordering data

Version	Suitable for	Lamp voltage	Color	Order no.	List Price
					\$
Lamps with screw connection, miniature bayonet (BA 9s style)					
Incandescent lamps,					
	Flashing, type 267 lamp (replaces 755 lamp)	51, 52	6 V AC	52AABNF	12.40
	6V type 755 lamp	51, 52	6 V AC	52AABN	8.20
	12V type 756	51, 52	12 V AC	52AACN	8.20
	24V type 757	51, 52	24 V AC	52AADN	7.50
	120V, 2.5W, type #120MB	52	120V AC	52AAENC1	8.20
	Neon (uses resistors) type B2A (NE-51H)	52	120 V AC	52AAPN	16.90
	48V	51, 52	48 V	3SB1902-1AP	12.50
Candelabra, 120 V, Full voltage type 3S6/5¹	52 older revision styles	120 V		52AAENC	8.20
7 Watts					
LED's BA9s Style length 28 mm diameter 10 mm current 15 ma	52	6 V UC	red	52AEB2	22.50
	52	6 V UC	green	52AEB3	22.50
	52	6 V UC	yellow	52AEB4	22.50
	52	6 V UC	white	52AEBB	22.50
	52	6 V UC	blue	52AEB5	22.50
	52	24 V UC	red	52AED2	22.50
	52	24 V UC	green	52AED3	22.50
	52	24 V UC	yellow	52AED4	22.50
	52	24 V UC	white	52AEDB	22.50
	52	24 V UC	blue	52AED5	22.50
	52	120 V AC	red	52AEE2	22.50
	52	120 V AC	green	52AEE3	22.50
	52	120 V AC	yellow	52AEE4	22.50
	52	120 V AC	white	52AEEB	22.50
	52	120 V AC	blue	52AEE5	22.50
LED's, cluster type For use with Class 52 pilot lights only (7 LED's)	52	6 V UC	red	52AEB27	28.00
	52	6 V UC	green	52AEB37	28.00
	52	6 V UC	yellow	52AEB47	28.00
52	24 V UC	red	52AED27	28.00	
52	24 V UC	green	52AED37	28.00	
52	24 V UC	yellow	52AED47	28.00	
52	120 V AC	red	52AEE27	28.00	
52	120 V AC	green	52AEE37	28.00	
52	120 V AC	yellow	52AEE47	28.00	

Touchsafe contact blocks with gold flashing



52 BAJ



52 BAK



52 BAR

		Plunger Color		
1 NO		White	52BAK	12.40
1 NC		Red	52BAJ	12.40
1 NO - 1 NC		Black	52BJK	24.50
1 NO early make	closes before 52BAK opens after 52 BAJ	Green	52BAH	12.40
1 NC late break		Yellow	52BAE	12.40
1 NO - 1 NC		—	52BAR²⁾	49.50
	UL listed for class 1 division 2 .25A Max, 200V AC, 10 Watt max .5A Max, 200V DC, 10 Watt max			
1 NC extra late break		Blue	52BAU	12.40
1 NO	Not touch safe		52BAKE	15.40
1 NC	Not touch safe		52BAJE	15.40

1) Design change made in 2003 from candelabra to BA 9s type bulbs. Contact technical support for further information.

2) Hermetically sealed.