

# Product: <u>5301FE</u> ☑

Security & Sound, 3 Conductor 18 AWG, BC, O/A Foil, CMR



### **Product Description**

Security & Commercial Audio Cable, Riser-CMR, 3-18 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

### **Technical Specifications**

Suitable Applications:					Intercom/PA S	Systems,	Sound/Audio S	/stems		
Physical C	harac	teristics	(Overa	all)						
Conductor										
Element	AWG	Stranding	Mat	terial	No. o	of Conductors				
Conductor(s)	18	7x26	BC - Ba	re Copper	3					
Conductor Co	unt:					3				
sulation										
Element	M	aterial	Nomin	al Wall Th	icknes	ss				
Conductor(s)	PP - Pc	lypropylene	e 0.008 i	n						
olor Chart										
Number Col	or									
1 Blac										
2 Rec	t									
3 Whi	ite									
3 Whi Duter Shield M Type Mater	ite Naterial	nterial Trad	e Name	Coverage	e [%]	Drainwire Ma	terial D	Drainwire AWG	Drainwire C	construction n x
3 Whi Duter Shield M Type Mater	ite Naterial fial Ma	iterial Trad	e Name	Coverage 100 %		Drainwire Ma TC - Tinned C			Drainwire C 7x32	Construction n x
3 Whi Duter Shield M Type Mater Tape Alum / Poly	ite Material Fial Ma Be		e Name							ionstruction n x
3 Whi Puter Shield M Type Mater Tape Alum / Poly Poly	ite Naterial Tial Ma Be Naterial	ldfoil®		100 %		TC - Tinned C	opper 2	24		construction n x
3 Whi Duter Shield N Type Mater Tape Alum / Poly Duter Jacket N Mater	ite Material Material Material ial	Idfoil® Nomina	al Diame	100 % ter Nomin	nal Wa		opper 2	24		construction n x
3 Whi Duter Shield N Type Mater Tape Alum / Poly Duter Jacket N Mater	ite Material Material Material ial	Idfoil® Nomina	al Diame	100 %	nal Wa	TC - Tinned C	opper 2	24		Construction n x
3 Whi Duter Shield N Type Mater Tape Alum / Poly Duter Jacket N Mater PVC - Polyviny	ite Material Material Material ial	ldfoil® Nomina de 0.171 in	al Diame	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		onstruction n x
3 Whi Duter Shield N Type Mater Tape Alum / Poly Duter Jacket N Mater PVC - Polyving Construction	ite Material Material Material ial	ldfoil® Nomina de 0.171 in	al Diame	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		Construction n x
3 Whi Duter Shield M Type Mater Tape Alum / Poly Duter Jacket M Materi PVC - Polyving Construction Cabling	ite Material Material ial yl Chlorid	ldfoil® Nomina de 0.171 in	al Diame	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		Construction n x
3 Whi Duter Shield M Type Mater Tape Alum / Poly Duter Jacket M Materi PVC - Polyving Construction Cabling Lay Direction	ite Material Material ial yl Chlorid on and	Idfoil® Nomina de 0.171 in d Dimens	al Diame	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		Construction n x
3 Whi Type Mater Tape Alum / Poly  Duter Jacket M Materi PVC - Polyving  Construction  abling Lay Direction	ite Material Material ial yl Chlorid	Idfoil® Nomina de 0.171 in d Dimens	al Diame	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		onstruction n x
3 Whi Type Mater Tape Alum / Poly Duter Jacket M Mater PVC - Polyvin Construction Lay Direction Left Hand	ite Material Material ial yl Chlorid on and Twis 4.8 twi	Idfoil® Nomina de 0.171 in d Dimens ts st/ft	al Diame n sions	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		Construction n x
3 Whi Type Mater Tape Alum / Poly Duter Jacket M Mater PVC - Polyvin Construction tabling Lay Direction Left Hand	ite Material Material ial yl Chlorid on and Twis 4.8 twi	Idfoil® Nomina de 0.171 in d Dimens ts st/ft	al Diame n sions	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		Construction n x
3 Whi Duter Shield M Type Mater Tape Alum / Poly Duter Jacket M	ite Material	Idfoil® Nomina de 0.171 in d Dimens ts st/ft	al Diame n sions	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		Construction n x
3 Whi Type Mater Tape Alum / Poly Outer Jacket N Mater PVC - Polyvin Construction Laty Direction Left Hand Electrical C	ite Material Material Material ial yl Chlorid On and 4.8 twi Charac R	Idfoil® Nomina de 0.171 in d Dimens ts st/ft st/ft	al Diamer	100 % ter Nomin	nal Wa	TC - Tinned C	opper 2	24		onstruction n x

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
36 pF/ft	64.75 pF/ft

#### Current

Element	Max. Recommended Current [A]
10C Temperature Rise	Per conductor @ 25°C ambient: 5 A

#### Voltage

UL Voltage Rating 300 V RMS

### **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

## **Mechanical Characteristics**

Bulk Cable Weight:	24 lbs/1000ft
Max Recommended Pulling Tension:	81.2 lbs
Min Bend Radius/Minor Axis:	1.625 in

#### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

## Applicable Environmental and Other Programs

Environmental Space:	Indoor - Riser
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:

Yes

### Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1666 Vertical Shaft
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6301FE

#### Part Number

#### Variants

ltem #	Color	Putup Type	Length	UPC/EAN
5301FE.00305	Chrome	Reel	305 m	8719605008206
5301FE 008500	Gray	Reel	500 ft	612825336815
5301FE 008U500	Gray	UnReel	500 ft	612825425564
5301FE 0081000	Gray	Reel	1,000 ft	612825336839
5301FE 008U1000	Gray	UnReel	1,000 ft	612825159438
5301FE 008Z1000	Gray	ReelTuff Box	1,000 ft	612825159452

Footnote:

#### C - CRATE REEL PUT-UP.

#### **History**

Update and Revision:

#### Revision Number: 0.279 Revision Date: 05-11-2020

#### © 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.