


SKINTOP® MS-NPT/MSR-NPT

Nickel-Plated Brass Strain Relief with NPT Thread

Complete the Installation

 SKINTOP® DIX Bushing
page 537

 Plugs
page 540



SKINTOP® MS-NPT/MSR-NPT is a superior quality, liquid-tight, metallic cable gland intended for applications where ruggedness and durability are required. These cable glands are suitable for a wide range of applications, from manufacturing machinery to measurement and control equipment, including automation and robotics.

Approvals



Application Advantage

- Suitable for use in areas with high demands on mechanical and chemical stability
- The heavy duty SKINTOP® design provides great pull-out strength and very reliable strain relief
- Extended temperature range due to the nickel-plated brass body
- Generous high-quality neoprene bushing and perbunan O-ring provide a liquid-tight and dust-proof hermetic seal

Technical Data

Material:

- Body: Nickel-plated brass
- Insert: Polyamide
- Bushing: CR
- O-ring: NBR

Temperature Range:

- Static: -40°C to +100°C
- Dynamic: -25°C to +100°C

IP Protection:

IP68, 5 bar
(Exceeds NEMA 6/6P pressure rating)

Locknuts: Add SM locknuts, page 534

Part Number	Thread Type & Size	øF Clamping Range (in) (mm)		SW Wrenching Flats (in)	C Overall Length (in)	D Thread Length (in)	Standard Pack Size
SKINTOP® MS-NPT: Standard							
53112004	NPT ¼"	0.137 - 0.275	3.5 - 7.0	0.630	1.418	0.591	100
53112014	NPT ⅜"	0.177 - 0.394	4.5 - 10.0	0.788	1.564	0.591	100
53112024	NPT ½"	0.275 - 0.512	7.0 - 13.0	0.945	1.674	0.591	50
53112034	NPT ¾"	0.354 - 0.669	9.0 - 17.0	1.142	1.753	0.591	25
53112044	NPT 1"	0.433 - 0.827	11.0 - 21.0	1.418	1.930	0.591	25
53112054	NPT 1¼"	0.748 - 1.103	19.0 - 28.0	1.773	2.265	0.669	10
53112064	NPT 1½"	1.063 - 1.379	27.0 - 35.0	2.127	2.423	0.669	5
53112074	NPT 2"	1.339 - 1.773	34.0 - 45.0	2.639	2.501	0.669	5
SKINTOP® MSR-NPT: Reducer Bushing							
53112006	NPT ¼"	0.039 - 0.197	1.0 - 5.0	0.630	1.418	0.591	100
53112016	NPT ⅜"	0.078 - 0.275	2.0 - 7.0	0.788	1.564	0.591	100
53112026	NPT ½"	0.197 - 0.394	5.0 - 10.0	0.945	1.674	0.591	50
53112036	NPT ¾"	0.236 - 0.512	6.0 - 13.0	1.142	1.753	0.591	25
53112046	NPT 1"	0.275 - 0.591	7.0 - 15.0	1.418	1.930	0.591	25
53112056	NPT 1¼"	0.591 - 0.906	15.0 - 23.0	1.773	2.265	0.669	10
53112066	NPT 1½"	0.866 - 1.142	22.0 - 29.0	2.127	2.423	0.669	5
53112076	NPT 2"	1.103 - 1.536	28.0 - 39.0	2.639	2.501	0.669	5

Photographs are not to scale and are not true representations of the products in question.

If not otherwise specified, all values relating to the product are nominal values. For current information go to our website.