



基板取付穴推奨寸法

★ T 1.6 ±

31.9	30.3	28.3	25	53251-1110	11
29.4	27.8	25.8	22.	-1010	10
24.4	22.8	20.8	17.5	-0810	8
19.4	17.8	15.8	12.5	-0610	6
16.9	15.3	13.3	10	53251-0510	5
D	C	B	A	ENG. NO.	極数

注記

- 嵌合相手: 51064-\*\*-00
- キンは両端のソルダテールのみとする。
- ウエハー: ポリエステル, UL94V-0 (WHITE)  
ピン: 磷青銅, 錫メッキ ±=0.4

材料 MATERIAL		注記参照		molex MOLEX-JAPAN CO.,LTD. 日本モレックス株式会社	
仕上げ FINISH		---		EDP. NO.	
適用電線範囲 WIRE RANGE		---		ENG. NO. SD-53251-**-10	
被覆外径 INS. RANGE		---		REV. C	
DRAWN BY '89/9/26 K.FURUYAMA		CHK'D BY M.SAKANO		TITLE 名称 2.5 WIRE TO BOARD CONN. W/POSITIVE LOCK WAFER ASSY	
APP'D BY M.ENOMOTO		尺度 SCALE 5-1			

角度 ANGLE	±3°
30以上 OVER	+0.3
10以上 30未滿 UNDER	+0.25
10未滿 UNDER	+0.2
一般公差 GENERAL TOLERANCES	

REVISE ONLY ON CAD SYSTEM