

Liquidtight Flexible Metal Conduit Fittings T&B Catalog Number:

5331GR

UPC Number: 78621089997

Status: Active

Description:

3/8 Inch Steel External Bonding Liquidtight Insulated Connector

Features

| i catures | |
|-----------------------|---|
| | Ability to install quickly with low torque effort |
| Application | |
| | To positively bond conduit to box or enclosure |
| General | |
| Trade Size (inches) | 3/8 |
| Material | Steel |
| Finish | Electro Zinc Plated/Chromate Coating |
| Ground Wire | 14-8 |
| Dimension Information | |
| Dimension A (inches) | 4.5/00 |
| Dimension A (inches) | 1 5/32 |
| Dimension B (inches) | 1 1/2 |
| Dimension C (inches) | 9/16 |
| Specifications | |
| 3dmodel | Available on Website |
| Packaging | |
| T&B Inner Pack | 25 |
| Package in Units | 100 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 16 lbs. per 100 |
| Certifications | |
| RoHS Compliance | Yes |
| Certifications | |
| | |



File Nbr: E 3060

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com