



Industrial grade straight blade devices

Product description

2-pole, 3-wire grounding
20A, 250V/AC
NEMA 6-20



5466N



5879C



AH5469BK

Industrial grade plugs & connectors



Rating		NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
A	V/AC							
20	250	6-20	Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	□ AH5466	□ AH5469	• •
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	BK, Y	□ AH5464__	□ AH5469__	•
			Auto grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	□ 5466N	□ 5469N	• •

Industrial grade flanged inlets & outlets



Rating		NEMA	Description	Color	Inlet catalog no.	Outlet catalog no.	
A	V/AC						
20	250	6-20	Nylon construction, back wire	BK & W	□ 5878C	□ 5879C*	• •

* UL Listed only

Industrial grade dimensional information: B-16, B-17

Specification information:

Safety grip industrial plugs & connectors: B-24
Quick grip plugs & connectors: B-24
Auto grip industrial plugs & connectors: B-24
Industrial flanged inlets & flanged outlets: B-25

Color information:

BK (Black), W (White), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32