



Representative

Catalog Number: Product ID: UPC Number: EAN Number: Status: **54820** 7TAH007510R0017 78621054820 05414363110866 Active

Copper Two-Way Splice, Long Barrel, Max 35kV, Wire Size 600 kcmil, 444 kcmil Flex, Length 4.25 Inches, Tin Plated, Die Code 94, Die Color Code Green

• Two-way connectors provide high pullout values, are easy to insulate and provide a low-resistance connection of high quality and low installed cost.

## North American Specifications (UNSPSC)

IGCC4669 Wire or cable compression spliceBrand NameColor-KeyedTypeSplice ConnectorSpecial FeaturesTwo-way connectors provide high pullout values, are easy to insulate and provide a low-resistance connection of high quality and low installed cost.StandardUL E9809, CSA 4503MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Dimensions (inches)23.6x11x3.9		
Brand NameColor-KeyedTypeSplice ConnectorSpecial FeaturesTwo-way connectors provide high pullout values, are easy to insulate and provide a low-resistance connection of high quality and low installed cost.StandardUL E9809, CSA 4503MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VPackaging4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	UNSPSC	39121449 Wire or cable compression splice
TypeSplice ConnectorSpecial FeaturesTwo-way connectors provide high pullout values, are easy to insulate and provide a low-resistance connection of high quality and low installed cost.StandardUL E9809, CSA 4503MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VPackagingInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	IGCC	4669 Wire or cable compression splice
Special FeaturesTwo-way connectors provide high pullout values, are easy to insulate and provide a low-resistance connection of high quality and low installed cost.StandardUL E9809, CSA 4503MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Dimensions (inches)23.6x11x3.9	Brand Name	Color-Keyed
are easy to insulate and provide a low-resistance connection of high quality and low installed cost.StandardUL E9809, CSA 4503MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VPackagingInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Dimensions (inches)23.6x11x3.9	Туре	Splice Connector
connection of high quality and low installed cost.StandardUL E9809, CSA 4503MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VPackagingInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	Special Features	Two-way connectors provide high pullout values,
StandardUL E9809, CSA 4503MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VPackagingInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9		are easy to insulate and provide a low-resistance
MaterialCopperFinishTin-PlatedColorGreenVoltage Rating600VPackagingInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9		connection of high quality and low installed cost.
FinishTin-PlatedColorGreenVoltage Rating600VPackagingInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	Standard	UL E9809, CSA 4503
ColorGreenVoltage Rating600VPackaging6Inner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	Material	Copper
Voltage Rating 600V   Packaging 6   Inner Quantity 6   Inner Dimensions (inches) 4.9x4.3x3.2   Outer Quantity 60   Outer Dimensions (inches) 23.6x11x3.9	Finish	Tin-Plated
PackagingInner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	Color	Green
Inner Quantity6Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	Voltage Rating	600V
Inner Dimensions (inches)4.9x4.3x3.2Outer Quantity60Outer Dimensions (inches)23.6x11x3.9	Packaging	
Outer Quantity 60   Outer Dimensions (inches) 23.6x11x3.9	Inner Quantity	6
Outer Dimensions (inches) 23.6x11x3.9	Inner Dimensions (inches)	4.9x4.3x3.2
	Outer Quantity	60
Weight Uom 56.5 lbs. per 100	Outer Dimensions (inches)	23.6x11x3.9
	Weight Uom	56.5 lbs. per 100

## **Documents / Support Tools**

Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website
Instruction Sheet 1	ta00674-tb2

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com