



- Circuit Board Indicators
- Panel Mount Indicators
- Solid State Lighting
- Traffic Signals
- Vehicle Lighting
- Rail
- Obstruction Lighting
- Hazardous Area Lighting
- Heliport Lighting

how to purchase

-  sales contacts
-  stock check

search

 Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

Part # / Text Search

Part No.:

Text Search:

search

quick links

Dialight Corporate Video


Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

Dialight Ltd (UK)
 Dialight Garufo
 Dialight BLP
 LumiDrives

Circuit Board Indicators - Through Hole Indicators		
P/N# 5511409F	3 mm Lens Single Color	
Description	3 mm CBI Right Angle	
Package Options	100 Pieces Per Bag	
Product Type	Through Hole Indicators	
Sub Product Type	with Single Housing	
Configuration	3 mm Lens	
Lamp Type	Single Color	
Viewing	Right Angle	
Viewing Angle	45	
Test Current (mA)	1mA	
Forward Current (mA)	30mA	
LED Centerline	3.05	
Polarity	Cathode Right	

Absolute Maximum Ratings (Ta = 25 °)		
Derating	from 50Â° @ .5 mA/Â°C	
Reverse Voltage	5 V	
Solder Temp	260Â° for 5 sec	
Operating Temp	-20 to +100° C	
Storage Temp	-55 to +100° C	



Operating Characteristics		
LED Position		
Color	Red	
Lamp Type	Single Color	
LED Type	Low Current	
Intensity Min (mcd)	2	
Intensity Typ (mcd)	3.0	
Intensity Max (mcd)		
Fwd Voltage Min		
Fwd Voltage Typ		
Fwd Voltage Max		
Dom Wavelength Min (nm)		
Dom Wavelength Typ (nm)		
Dom Wavelength Max (nm)		
Power Dissipation Max (mW)	87	
Backlighting		
Pitch Between Vertical		
Pitch Between Horizontal		
Lum Intensity Min		
Lum Intensity Typ		
Lum Intensity Max		

Distributor Stock Check

Check stock with our distributors now.

5511409F

check stock