



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

- how to purchase*
- [sales contacts](#)
  - [stock check](#)

[Product Line Search](#)

Please select a Product Line to search.

▼

[Part # / Text Search](#)

Part No.:

Text Search:


- [quick links](#)
- Dialight Corporate Video**
- [Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. \*\*View PDF File\*\*](#)
- Application Notes**  
[FAQs](#)
- Dialight Ltd (UK)**  
**Dialight Garufo**  
**Dialight BLP**  
**LumiDrives**

## Circuit Board Indicators - Through Hole Indicators

<b>P/N# 5690101372F</b>	<b>3 mm Lens</b>
Description	3 mm Dual Bi-Level CBI R-Y-O-G
Package Options	50 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	with Bi-Level Housing
Configuration	3 mm Lens
Viewing	Right Angle
Viewing Angle	60
Test Current (mA)	10mA

### Absolute Maximum Ratings (T<sub>a</sub> = 25 °)

Solder Temp	<b>260Å° for 5 sec</b>
Operating Temp	<b>-55 to +100° C</b>
Storage Temp	<b>-55 to +100° C</b>



### Distributor Stock Check

**Check stock with our distributors now.**

## Operating Characteristics

LED Position	Found in position(s): 1	Found in position(s): 2	Found in position(s): 3	Found in position(s): 4
Color	Red	Yellow	Orange	Green
Lamp Type	Single Color	Single Color	Single Color	Single Color
LED Type	Standard Efficiency	Standard Efficiency	Standard Efficiency	Standard Efficiency
Intensity Min (mcd)	7.4	7.4	3.4	4.7
Intensity Typ (mcd)	10.0	10.0	7.0	12.6
Intensity Max (mcd)			10.8	
Fwd Voltage Min				
Fwd Voltage Typ				
Fwd Voltage Max				
Dom Wavelength Min (nm)			602	
Dom Wavelength Typ (nm)				
Dom Wavelength Max (nm)				
Power Dissipation Max (mW)	100	60	135	100
Backlighting				
Pitch Between Vertical				
Pitch Between Horizontal				
Lum Intensity Min				
Lum Intensity Typ				
Lum Intensity Max				