

[Home](#) > [569 -0704 -444F](#)


Search For Part Number

Part Number: **5690704444F**

| General Description | |
|---------------------|--|
| Series | 569 |
| Configuration | 3 mm Lens |
| Description | 3 mm Dual Bi -Level CBI Y/G -Y/G -Y/G -Y/G |
| Package Options | Bulk Packaging |
| Sizes | 3mm |
| Lamp Type | Bi-Level Housing |
| Viewing | Right Angle |
| Polarity | Cathode Pin 1 & 3 |
| Lens Style | Untinted, Diffused |
| Viewing Angle | 80 |
| LED Centerline | 2.29mm |

| Absolute Maximum Ratings (Ta = 25Å °) | |
|---------------------------------------|----------------|
| Solder Temperature | 260 for 5 secs |
| Operating Temperature | -55 to +100 |
| Storage Temperature | -55 to +100 |

| Operating Characteristics | | |
|----------------------------|-----------------------|-------|
| | LED Position: 1,2,3,4 | |
| Color | Yellow | Green |
| Peak Wave Length | 585 | 565 |
| Luminous Intensity Min | 2.5 | 2.5 |
| Luminous Intensity Typical | 4.3 | 6.3 |
| Forward Voltage Typical | 2.1 | 2.1 |
| Forward Voltage Max | 2.8 | 2.8 |
| Power Dissipation Max | 60mW | 100mW |



5690704444F

[check stock](#)



[This is a RoHS Compliant Product](#)
[To learn more click here](#)