


59020 Mini Firecracker Features and Benefits



Features

- 2 part magnetically operated proximity sensor
- Normally open contact
- Customer defined sensitivity
- Choice of cable length and connector


Benefits

- Quick and easy to install
- No standby power requirement
- Operates through non-ferrous materials such as wood, plastic or aluminium
- Hermetically sealed, magnetically operated contacts continue to operate long after optical and other technologies fail due to contamination

Applications

- Position and limit sensing
- Security
- Level sensing
- Linear actuators

DIMENSIONS (in) mm



	A Max	B Max	C NOM.
57020	(.201) 5,10	(.600) 15,24	-
59020	(.201) 5,10	(.600) 15,24	Table 3 ± (.393) 10,00


CUSTOMER OPTIONS - Switching Specifications

TABLE 1			Normally Open
Contact Type			I
Switch Type			I
Power	Power	Watt - max.	10
	Switching	Vdc - max.	170
Voltage	Breakdown	Vdc - min.	175
	Switching	A - max.	0.5
Current	Carry	A - max.	0.5
	Contact, Initial	Ω - max.	0.2
Resistance	Insulation	Ω - min.	10 ¹⁰
	Contact	pF - typ.	0.2
Capacitance	Operating	°C	-40 to +105
	Storage	°C	-65 to +105
Temperature	Operate	ms - max.	1.0
	Release	ms - max.	1.0
Time	I 1 ms I/2 sine	G - max.	100
Shock	50-2000 Hz	G - max.	30
Vibration			

CUSTOMER OPTIONS - Sensitivity, Cable Length and Termination Specification

TABLE 2							TABLE 3		TABLE 4																																			
Sensitivity Options:- Activate Distances are approximate using Hamlin 57020 actuator as illustrated. Switch AT before modification							Cable Type:- 26 AWG 7/34 PVC 105°C UL1430/UL1569		Termination Options:-																																			
							Standard Lengths		<table border="1"> <thead> <tr> <th>SELECT OPTION</th> <th>DESCRIPTION</th> <th></th> </tr> </thead> <tbody> <tr> <td>A</td> <td>Tinned leads</td> <td></td> </tr> <tr> <td>B</td> <td>Crimped terminals</td> <td></td> </tr> <tr> <td>C</td> <td>6.35mm fastons</td> <td></td> </tr> <tr> <td>D</td> <td>AMP MTE 2.54mm pitch</td> <td></td> </tr> <tr> <td>E</td> <td>JST XHP 2.5mm pitch</td> <td></td> </tr> </tbody> </table>			SELECT OPTION	DESCRIPTION		A	Tinned leads		B	Crimped terminals		C	6.35mm fastons		D	AMP MTE 2.54mm pitch		E	JST XHP 2.5mm pitch																
SELECT OPTION	DESCRIPTION																																											
A	Tinned leads																																											
B	Crimped terminals																																											
C	6.35mm fastons																																											
D	AMP MTE 2.54mm pitch																																											
E	JST XHP 2.5mm pitch																																											
<table border="1"> <thead> <tr> <th>Select Option</th> <th colspan="2">S</th> <th colspan="2">T</th> <th colspan="2">U</th> </tr> <tr> <th>Switch Type</th> <th>Pull In AT Range</th> <th>Activate Distance d (in) mm</th> <th>Pull In AT Range</th> <th>Activate Distance d (in) mm</th> <th>Pull In AT Range</th> <th>Activate Distance d (in) mm</th> </tr> </thead> <tbody> <tr> <td>I</td> <td>Normally Open</td> <td>6-10 (.236) 6,0</td> <td>10-15 (.177) 4,5</td> <td>13-19 (.157) 4,0</td> <td></td> <td></td> </tr> </tbody> </table>							Select Option	S		T		U		Switch Type	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm	I	Normally Open	6-10 (.236) 6,0	10-15 (.177) 4,5	13-19 (.157) 4,0			<table border="1"> <thead> <tr> <th>SELECT OPTION</th> <th>CABLE LENGTH (in) mm</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>(3,94) 100</td> </tr> <tr> <td>02</td> <td>(11,81) 300</td> </tr> <tr> <td>03</td> <td>(19,69) 500</td> </tr> <tr> <td>04</td> <td>(29,53) 750</td> </tr> <tr> <td>05</td> <td>(39,37) 1000</td> </tr> </tbody> </table>		SELECT OPTION	CABLE LENGTH (in) mm	01	(3,94) 100	02	(11,81) 300	03	(19,69) 500	04	(29,53) 750	05	(39,37) 1000			
Select Option	S		T		U																																							
Switch Type	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm	Pull In AT Range	Activate Distance d (in) mm																																						
I	Normally Open	6-10 (.236) 6,0	10-15 (.177) 4,5	13-19 (.157) 4,0																																								
SELECT OPTION	CABLE LENGTH (in) mm																																											
01	(3,94) 100																																											
02	(11,81) 300																																											
03	(19,69) 500																																											
04	(29,53) 750																																											
05	(39,37) 1000																																											

ORDERING INFORMATION



Hamlin USA Tel: +1 920 648 3000 • Fax: +1 920 648 3001 • Email: sales.us@hamlin.com
Hamlin UK Tel: +44 (0) 1379 649700 • Fax: +44 (0) 1379 649702 • Email: sales.uk@hamlin.com
Hamlin Germany Tel: +49 (0) 6181 953660 • Fax: +49 (0) 6181 953666 • Email: sales.de@hamlin.com
Hamletrol France Tel: +33 (0) 1 4687 0202 • Fax: +33 (0) 1 4686 6786 • Email: sales.fr@hamlin.com

DETAILS PROVIDED ON THIS DATA SHEET ARE PROVIDED FOR INFORMATION PURPOSES ONLY AND SHOULD NOT BE RELIED UPON AS BEING ACCURATE FOR ANY PARTICULAR PURPOSE. Product performance may be affected by the application to which the product is put. Upon request, HAMLIN will assist purchasers by providing information specific to any particular application. HAMLIN disclaims any and all liability whatsoever for any purchaser's reliance upon the information contained on this data sheet without further consultation with authorised representatives of HAMLIN.