Honeywell

Honeywell Sensing and Control

Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback



Home> Products > MICRO SWITCH™ Sealed and High Accuracy Switches > AT > Product Page

62AT11-3

AT Series Toggle Switch, 2 pole, 2 position, Solder T2 type terminal, **Standard Lever**

Actual product appearance may vary.

Features

Gold or silver contacts Choice of sealed bushing Standard or pull to unlock toggle lever Short behind-panel depth Solder or quick connect termination 2,4, 6, or 8 SPDT precision basic switches 2 or 3 position, momentary or maintained action

Potential Applications

Industrial machinery and equipment Military and commercial aviation Construction equipment Test instruments Agricultural machinery Process control Medical instrumentation

My Links Login to iCOM Login as Rep/AD Login as Guest Login to Digital University **Keyword Search** Search for product and support information. All Sensing and Contre **Product Search** Part number search:

Use (*) to expand search

Specification Search

Description

Compact multipole 2, 4, 6,or 8 SPDT design. MICRO SWITCH™ precision basic switches conserve space and weight. Pull -to-Unlock Toggle Levers prevent accidental operation: the lever must be pulled approximately 2,3 mm [0.09 inches] to change the positions. Many locking configurations are available. Lever to bushing seals. Hermetic basic switches are available. AT qualified versions meet MILS-8805/98. Various levers and styles are available.

itout Accessory: Seals	
Product Specifications	
Maintained Maintained NC COM NO NC COM NO NC COM NO NC COM NO ON	
MICRO SWITCH™ Toggle	
0.1 A to 7.0 A at 0.5 Vdc to 28 Vdc	
DPDT	
2 position	
Bushing 15/32 in	
Solder T2 type	
Contains 1SX1 - T2 basic switches	
Global	
30211908	
30211908 Toggle switches	
AT	