



Home > Products > MICRO SWITCH™ Toggle Switches > NT > Product Page

62NT1-7



Actual product appearance may vary.

NT Series Toggle Switch, Panel stand - off feature, 2 pole step base, 3 position, Screw terminal, Standard Lever

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

Features

Completely sealed switching chamber
NEMA 3, 3R, 4, and 13
UL recognized, File E12252, Vol. 1, Section 44
CSA certified, File LR4442
CE approved

Potential Applications

Aerial lifts, scissor lifts, truck mounted tele-handlers, and cranes
Construction equipment
Agriculture equipment
Material-handling equipment
Factory-floor control units
Machine tool equipment manufacturers

Description

MICRO SWITCH™ NT Series toggle switches meet the need for a rugged, cost effective toggle switch. Quality construction features include a seal between the toggle lever and bushing, and between the cover and case. These switches can be used where panels are subject to splashes, hosedowns, or outdoor environments. The "Easy-Start" threaded bushing enables quick alignment of mounting nut to decrease the chance of cross threading. The panel stand-off with O-ring feature available on some listings, eliminates the need for behind-the-panel hardware, provides uniform panel height, and provides a panel to cover seal.

Supporting Documentation

- [Accessory: Lever Sleeve](#)
- [Terminal Identification](#)
- [Accessory: Seals](#)
- [Panel Cutout](#)
- [Accessory: Nuts](#)
- [Engineering Drawing](#)

| Product Specifications | | |
|---------------------------------------|--|--|
| Circuitry/Operating action | Keyway Momentary Position 1 2 3 6 5 4 ON | Center Position 1 2 3 6 5 4 OFF |
| | Opposite Keyway Momentary Position 1 2 3 6 5 4 ON | |
| Product Type | MICRO SWITCH™ Toggle Switch | |
| Ampere/Voltage Range (Resistive Load) | 0.5 A to 18 A at 0.5 Vdc to 28 Vdc, 0.75 A at 115 Vdc, 0.5 A to 10 A at 0.5 Vac to 277 Vac, 0.5 A at 250 Vdc | |
| Circuitry | DPDT | |
| Action | 3 position | |
| Mounting | Bushing 15/32 in | |
| Termination | Screw | |
| Lever Type | Standard | |
| UL/CSA Rating Code | L192: 10 A - 125, 250, 277 Vac; 1/4 Hp - 125 Vac; 1/2 Hp - 250, 277 Vac; 3 A - 125 Vac "L" | |
| Comment | Panel stand - off feature; Thermoplastic case | |
| Availability | Global | |
| UNSPSC Code | 30211908 | |
| UNSPSC Commodity | 30211908 Toggle switches | |
| Series Name | NT | |

My Links

- [Login to iCOM](#)
- [Login as Rep/AD](#)
- [Login as Guest](#)
- [Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search