

Screwdrivers

STANLEY
FatMax



New

- High grade steel bar for high torque and reduces the chance of tip breakage
- Slip-resistant rubber grip
- Impact-tough handle is overmoulded onto bars for greater torque
- Colour coded ends for easy identification
- Sand blasted and heat treated tip for durability and precision

482981.467759

| Tip Size (mm) | Blade Length (mm) | Order Code | Price Each |
|-----------------|-------------------|------------|------------|
| Slotted | | | |
| 2.5 | 50 | 145-4289 | |
| 3 | 100 | 145-4290 | |
| 3.5 | 75 | 145-4291 | |
| 3.5 | 100 | 145-4292 | |
| 4 | 30 (Stubby) | 145-4297 | |
| 4 | 100 | 145-4293 | |
| 5.5 | 30 (Stubby) | 145-4299 | |
| 5.5 | 125 | 145-4333 | |
| 5.5 | 150 | 145-4294 | |
| 6.5 | 30 (Stubby) | 145-4300 | |
| 6.5 | 150 | 145-4295 | |
| 6.5 | 250 | 145-4296 | |
| Phillips | | | |
| PH00 | 50 | 145-4301 | |
| PH0 | 75 | 145-4302 | |
| PH1 | 30 (Stubby) | 145-4310 | |
| PH1 | 100 | 145-4303 | |
| PH1 | 250 | 145-4305 | |
| PH2 | 30 (Stubby) | 145-4311 | |
| PH2 | 125 | 145-4306 | |
| PH2 | 250 | 145-4307 | |
| PH3 | 150 | 145-4308 | |
| PH4 | 200 | 145-4309 | |
| Pozidriv | | | |
| PZ0 | 75 | 145-4312 | |
| PZ1 | 30 (Stubby) | 145-4319 | |
| PZ1 | 100 | 145-4313 | |
| PZ1 | 250 | 145-4314 | |
| PZ2 | 30 (Stubby) | 145-4320 | |
| PZ2 | 125 | 145-4315 | |
| PZ3 | 150 | 145-4317 | |
| PZ4 | 200 | 145-4318 | |