HONEYWELL

See full Datasheet below...




BUY NOW



BUY NOW

masterelectronics.com & onlinecomponents.com are **authorized** e-commerce distributors of electronic components.



OPERATIN (C	ACTERI S	ISSUE		CATALOG		
	MIN	TYP	MAX	NO.	NUMBER	LISTING
OPERATE		352	575			
RELEASE	82	212		5	PR-2949	65\$\$4
DIFFERENTIAL	82	. 140				
OPERATE		430	700			
RELEASE	100	260		5	PR-2949	65SS2 _.
DIFFERENTIAL	100	170				
OPERATE						
RELEASE						
DIFFERENTIAL						
OPERATE						
RELEASE	-					-
DIFFERENTIAL						

ABSOLUTE MAXIMUM RATING

SUPPLY VOLTAGE (V _S)	(-)1.2 VOLTS TO +10.0 VOLTS				
VOLTAGE EXTERNALLY APPLIED TO OUTPUT	+ 10.0 VOLTS MAX (OFF CONDITION ONLY) - 0.5 VOLTS MIN (ON OR OFF CONDITION)				
OUTPUT GURRENT	IO MA PER OUTPUT				
TEMPERATURE	– 40°C TO 100°C				
MAGNETIC FLUX	NO LIMIT. THE CIRCUIT CANNOT BE DAMAGED BY MAGNETIC OVERDRIVE				

ELECTRICAL CHARACTERISTICS

<u>\$</u>	MIN	TYP	MAX	REMARKS
SUPPLY CURRENT				