

# PHONE PLUGS & JACKS

Note: Unless otherwise specified, plug and jack exposed metal parts are normally bright nickel plated, Soldering tabs and lugs are usually tinned brass for best solder joints; except in case where gold or silver is used.

## ISOLATED PHONE JACKS

Plastic body for both 2.5mm & 3.5mm with solder terminals. Mount in 5/16" mounting hole (front mount) in panel up to 1/8" thick.



### 2.5 mm JACKS

**No. 70-626** - Mono (2 conductor)  
display package of one

**No. 70-626B** - Mono (2 conductor)  
bulk package

**No. 70-636** - Stereo (3 conductor)  
display package of one

**No. 70-636B** - Stereo (3 conductor)  
bulk packaged

### 3.5 mm JACKS

**No. 70-524** - Mono (2 conductor)  
display package of one

**No. 70-524B** - Mono (2 conductor)  
bulk package

**No. 70-534** - Stereo (3 conductor)  
display package of one

**No. 70-534B** - Stereo (3 conductor)  
bulk packaged

## TWO CONDUCTOR (MONO) MINIATURE PHONE JACKS

### TWO CONDUCTOR (MONO) MINIATURE PHONE JACK

Mounts in 1/4" hole panel thickness up to 3/32" Closed molded body, closed switching circuit; solder lug connections. Supplied with knurled round nut for mounting.

**No. 501JP** - display package of one  
**No. 501JPB** - bulk packaged



### TWO CONDUCTOR (MONO) MINIATURE PHONE JACK

Economy model miniature jack, closed circuit. Mounts in a 1/4" dia. hole in chassis up to 1/16" thick. Supplied with knurled, slotted round nut and washer.

**No. 702JP** - display package of one  
**No. 702J** - bulk packaged



## 2.5 MM (SUB MINIATURE) PHONE PLUGS

### STEREO 2.5mm PLUG

Solder lug. Overall length 1-1/4"

**No. 666PP** - package of two  
**No. 666P** - bulk packaged



### RIGHT ANGLE STEREO 2.5 mm PLUG

Black plastic body with molded strain relief. Solder terminals, maximum cable O.D. - 4.0 mm



**No. 70-093** - right angle, package of 1

**No. 70-093B** - right angle, bulk packaged

### MONO 2.5mm PLUG

2 conductor plug solder terminals 1" length, 3/32" dia. black.



**No. 660PP** - package of two  
**No. 660P** - bulk packaged

### RIGHT ANGLE MONO 2.5 mm PLUG

Black plastic body with molded strain relief. Solder terminals, maximum cable O.D. 4.0 mm.



**No. 70-091** - right angle, package of 1

**No. 70-091B** - right angle, bulk packaged

## 2.5 mm (SUB MINIATURE) PHONE JACKS

### STEREO 2.5mm Chassis Mount Jack

shielded, mounts in 15/64" hole for panel up to .075" thick



**No. 666JP** - package of two

**No. 666J** - bulk packaged

### STEREO 2.5mm JACK

Inline female, solder terminals.



**No. 666VP** - package of two

**No. 666V** - bulk packaged

### MONO 2.5mm JACK

Closed circuit female, mounts in 5/32" hole and panels up to 1/16" thick.



**No. 660JP** - package of two

**No. 660J** - bulk packaged

### MONO 2.5mm INLINE JACK

Solder contacts.



**No. 660VP** - package of two

**No. 660V** - bulk packaged

### KNURLED NUT TOOL



**No. NT500**

Tool is used to tighten slotted knurled nuts on 3.5mm and some 2.5mm jacks. (i.e. Nos. 502JB, 502KB. 501JR, 702J, 666J)