

PRODUCTS FOR ▼ BUSINESS	PRODUCTS FOR ▷ ABOUT US ▼ PARTICLES BY 3M ▷ CONSUMERS	Search Q
	er Foil Shielding Tape 1182, Double 18 yd (19.05 mm x 16.5 m), 12 per case	Ś
Part Number 1182-3/4"X18YD, 3M ID 80610882518, UPC 00051138496722		~
Quantinu	Copper foil backing with	th acrylic

Overview		• Copper foil backing with acr adhesive coating on both sid
Specifications		<ul> <li>Unique adhesive creates secu contact with the application surface</li> </ul>
Details Resources	4	• Suitable for bonding 2 surfact together physically and electrically
		• Tape measures 3/4 in x 18 yd 3.5 mil

**View Images** 

# des cure

- ces
- ds x

View all details

# **Specifications**

Agency Approvals	Flame Retardant , UL Recognized
Length	18 Linear Yard
Length (Metric)	16.5 m
Size	0.75 in. x 18 yd.
Thickness	3.5 mil
Thickness (Metric)	0.09 mm
Width	0.75 Inch
Width (Metric)	1.9

# **Details**

- Copper foil backing with acrylic adhesive coating on both sides •
- Unique adhesive creates secure contact with the application surface .
- Suitable for bonding 2 surfaces together physically and electrically •
- Tape measures 3/4 in x 18 yds x 3.5 mil
- Flame-retardant •
- Comes in amber color •

Help

.

- Comes on a removable liner for easy die-cutting and handling
- Rated for 600V applications
- UL Listed and RoHS 2011/65/EU Compliant
- 12 rolls/case

3M<sup>™</sup> Tape 1182 is a 3.5-mil thick, acrylic adhesive shielding tape. This flame-retardant tape is designed to bond 2 surfaces together physically and electrically. It comes on a removable liner for easy die-cutting and handling. The tape is rated for 600V dry applications.

3M<sup>™</sup> Tape 1182 Shielding Tape has deadsoft, copper foil backing with a pressure-sensitive, electrically conductive, acrylic adhesive coating on both sides that ensures firm adherence. The conductive particles in the adhesive offer low resistance between the substrate and the backing. The construction of the tape offers a good method of bonding and grounding conductive surfaces. UL Listed and RoHS 2011/65/EU Compliant.

# **Resources**

### **Brochures**

Tech Brief: Comparative Tracking Index Test (PDF, 532.2KB) Insulation for Transformer, Applications Guide (PDF, 415.0KB)

### **Data Sheets**

3M™ Copper Foil Conductive Tape 1182 Adhesive on Both Sides (PDF, 63.7KB)

#### Info

General Rules for Shelf Life Statements (VND.MS-EXCEL, 21.5KB)

# **3M United States**

PRODUCTS	INDUSTRIES	BRANDS
Abrasives	Automotive	Post-it
Adhesives & Tapes	Commercial Solutions	Scotch
Advanced Materials	Communications	Scotch-Brite
Films	Consumer	Command
Filtration	Design & Construction	Filtrete
View All Products	Electronics	Nexcare
	Energy	ScotchBlue
	Health Care	
	Manufacturing	
	Mining, Oil & Gas	
	Safety	
	Transportation	

#### HELP

Help Center Site Map

#### REGULATORY

SDS Search

Transport Information Search

RoHS & REACH Information Search

California Supply Chains Act Disclosure (PDF, 84KB)

UK Modern Slavery Act Statement (PDF, 169KB)

More Regulatory & Compliance Information

#### NEWS

News Center Particles by 3M Press Releases

#### **ABOUT US**

About 3M

**3M** Careers

**Investor Relations** 

Partners & Suppliers

Government Customers

Sustainability

**3Mgives** 

# SEARCH 3M

Search

## **FOLLOW US**





BINE Legal | Privacy | DMCA © 3M 2018. All Rights Reserved. The brands listed above are trademarks of 3M.

 $\nabla$