

Datasheet

Art.No. 70.358.1635.2

Hood BAS GOT GD 16 M32 50 A2

revos BASIC 500V size 16 hood with intermediate support M32, lateral cable entry, with double locking levers



Art.No.	70.358.1635.2
EAN	4015573651005
Order unit	1 pieces

Approvals



Technical data

General

Nominal voltage	500
Housing material	Aluminium
Colour	Grey
Surface	With powder coating
Degree of protection (IP)	Other
UV resistant	Yes
Inflammability class of insulation material acc. with UL94	Other
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Model

DIN-size	16
Model	male
Locking mechanism	Double locking levers
Cable entry	Sideways
Type of cable	Intermediate support
With cable screw gland	No
Thread size M	32
Hinged lid	No
EMC-version	No

Classification

ECLASS 8.1	27440202: Housing for industrial connectors
------------	---

ETIM 5.0	EC000437: Housing for industrial connectors
ETIM 4.0	EC000437: Housing for industrial connectors
ETIM 3.0	EC000437: Housing for industry plug connectors

Drawings

70.355.1635.5	BAS 60T 60 16 M32 A5	Kabelverschraubung (KV), IP65 /Cable gland (CG), IP65
70.355.1635.4	BAS 60T 60 16 M32 A4	KV mit Zugentlastung, IP54 /CG with strain relief, IP54
70.355.1635.3	BAS 60T 60 16 M32 A3	KV mit Zugentlastung und Krebschutz, IP54 /CG with strain relief and bend support, IP54
70.355.1635.2	BAS 60T 60 16 M25 A2	Zwischenstutzen /Bushing
70.355.1635.1	BAS 60T 60 16 M25 A1	Gezirkelbohrung /Thread hole
70.355.1635.0	BAS 60T 60 16 M25 A0	Kabelverschraubung (KV), IP54 /Cable gland (CG), IP54

Bestellnummer / Order number:

Typ / Type:

Varianten / Variants:

Weitere Daten, siehe KATALOG oder eKatalog. www.wieland-electric.com
Additional data see CATALOG or eCatalog. shop.wieland-electric.com

Wieland
Industrie- und
Energieelektronik

GEHAUSEOBERTEIL
Baugröße 16-Kabelabgang 5x11116-1635-M32
Hood size 16-cable outlet 5x11116-1635-M32