

Overview

Support

3M EMI Shielding Tapes are designed for applications requiring reliable point-to-point electrical contact, particularly EMI shielding, grounding and static charge draining. The tapes have a multitude of uses in electronic design and test laboratories for prototyping, design and troubleshooting. The 3M[™] Foil Shielding Tape Engineering Kit enables engineers who need only a few inches of a particular tape for specifying, prototyping, troubleshooting, testing and repairing to avoid the problems and expense associated with meeting minimum order quantities. The kit virtually eliminates the problem of rolls of tape lost between multiple users or kept loose in desk drawers.

Specifications

Adhesive Type	Conductive (1 sided)
Backing Material	Foil, Copper, Flat
China RoHS - Below MCV	Yes
EU RoHS Compliant	Yes
Material	Copper Foil
Metal Type	Smooth Copper Foil
Product Thickness	2.6 mil (66 microns)
Product Type	Copper Foil Tape with Acrylic Adhesive
Size	0.75 in. x 18 yd. (1.9 cm x 16.5 m)
Supplied on Liner	Yes
Tape Length	18 Linear Yard
Tape Length (metric)	16.5 m
Tape Total Thickness	2.6 Milli-inch
Tape Total Thickness (metric)	0,07 mm
Таре Туре	EMI Shielding
Tape Width	0.75 in
Tape Width (metric)	1.9 cm
Thickness	2.6 Millimetre



