

# TWILOCK, Straight Connector, Female Thread, for cable 11-17 mm 7.166.600.000

<b>cable diameter</b>	11 – 17 mm
<b>characteristic of connection</b>	Crimp Solder dip-solder (PCB)
<b>Contact material</b>	Copper-Zinc alloy
<b>Contact surface</b>	Nickel plated, Gold plated (0,25µm) Nickel
<b>for cables mm</b>	3 – 17 mm
<b>Housing material</b>	Copper-Zinc alloy Die Casting
<b>Housing surface</b>	other surface upon request Nickel plated brass
<b>Inserts</b>	PBT Fire protection class V-0 Thermoplastic Polyamid PA 6 (Nylon 6/6)
<b>Operating-Temperature</b>	-40 – 125 °C
<b>Protection category</b>	IP 67 / IP 69 K per EN 60 629 (connected)
<b>Seal ring</b>	Buna-N standard Viton (FKM)

intermatable with Speedtec

## Additional information

// [TWILOCK english](#)

[REQUEST 3D DATA](#)

[Certificates](#)

[ADD TO WATCHLIST](#)

[PRINT](#)

SUPPORT

### ELECTRIC COMPONENTS

- Circular Connectors
- Industrial Cable Glands
- Industrial Ex Cable Glands
- "Hazardous Areas" Cable Glands
- Conduit Systems
- Customized Projects

### HEATING EQUIPMENT

- Problem Fixer
- Fittings
- Designtechnic
- Boiler Connection
- Underfloor Heating
- Accessories, Spare Parts, Tools

### INFORMATION

- News
- Imprint
- Privacy Policy
- GTC

### NEWSLETTER

[SUBSCRIBE TO NEWSLETTER](#)

This website uses cookies to ensure you get the best experience on our website.

OK