




Set screw hubs



Ref. 724
3-Beam Relieved




Ref. 706 : 6-Beam Non-Relieved
Ref. 726 : 6-Beam Relieved




Typical


Clamp hubs



Ref. 725
3-Beam Relieved



Ref. 707 : 6-Beam Non-Relieved
Ref. 727 : 6-Beam Relieved



Typical

3-BEAM COUPLERS: DIMENSIONS & ORDER CODES

Coupler Type & Size	Set Screw Style	Clamp Style	ØD	L	L1	Bore Diameters			Set Screw	Cap Screw	2 Angular Offset Deg.	2 Parallel Offset mm	3 Peak Torque Nm	
						Min B1	Min B2	Max B1 & B2						
Relieved	06	724.06	6.4	12.7	3.2	1.0	2.0	3.0	M2	-	3	0.07	0.40	
	09	724.09	9.5	14.2	4.5	2.0	3.0	3.18	M2.5	M1.6		0.1		
		-	725.09											
	13	724.13	12.7	19.1	6.0	3.0	4.0	5.0	M3	M2	5	0.127	0.90	
		-	725.13											
	16	724.16	15.9	20.3	6.5			6.35	M4	M2.5			1.50	
		-	725.16											
	19	724.19	19.1	22.9		4.0	4.76	8.0					2.50	
		-	725.19											
	25	724.25	25.4	31.8	9.0	5.0	6.0	10.0	M5	M3			4.0	
	-	725.25												
32	724.32	31.8	44.5	12.0	6.0	8.0	14.0	M6	M4			6.0		
	-	725.32												

Materials

Couplers:
Aluminium L168 or better

Fasteners:
Alloy steel, black oiled

Temperature Range
-40°C to +120°C

All 3-beam couplers are in relieved form as standard. See above drawings.


BORE SIZES

Coupler Size	ØB1, ØB2 +0.03/-0mm														
	1	2	3	3.175	4	4.763	5	6	6.350	8	9.525	10	12	12.700	14
06	○	●	●												
09		○	●	●											
13			○	○	●	●	●								
16			○	○	●	●	●	●	●						
19				○	●	●	●	●	●	●					
25						○	●	●	●	●	●	●			
32							○	○	●	●	●	●	●	●	●
Bore ref.	08	11	14	16	18	19	20	22	26	28	31	32	35	36	38

HOW TO ORDER

Combine the COUPLER REF in Dimensions & Order Codes Table with BORE REFS in Bore Sizes Table. Please identify both bores e.g.

724.16.1924



○ B1 only ● B1 & B2

6-BEAM COUPLERS: DIMENSIONS & ORDER CODES

Coupler Type & Size	Set Screw Style	Clamp Style	ØD	L	L1	Bore Diameters			Set Screw	Cap Screw	Angular Offset Deg.	Parallel Offset mm	Peak Torque Nm
						Min B1	Min B2	Max B1 & B2					
Non-Relieved	09	706.09 -	9.5	19.6	5.3	2.0	4.0	4.76	M2.5	M1.6	3	0.12	1.0
	13	706.13 -	12.7	22.9	6.5	3.0	5.0	6.35	M3	M2	5	0.17	2.0
		707.09 707.13											
	16	706.16 -	15.9	25.4	6.5	3.0	6.0	8.0	M4	M2.5	5	0.2	3.4
		707.16											
	19	706.19 -	19.1	26.5	6.5	4.76	6.35	10.0	M4	M2.5	5	0.25	5.3
		707.19											
	25	706.25 -	25.4	38.1	6.5	4.76	6.35	10.0	M5	M3	5	0.38	10.0
		707.25											
	32	706.32 -	31.8	57.2	6.5	4.76	6.35	10.0	M6	M4	5	0.5	15.0
		707.32											
	38	706.38 -	38.1	66.7	6.5	4.76	6.35	10.0	M6	M5	5	0.6	22.0
		707.38											
	44	706.44 -	44.5	76.2	6.5	4.76	6.35	10.0	M6	M5	5	0.8	30.0
		707.44											
	51	706.51 -	50.8	95.3	6.5	4.76	6.35	10.0	M8	M6	5	0.9	40.0
707.51													
57	706.57 -	57.2	130.0	6.5	4.76	6.35	10.0	M8	M6	5	0.95	55.0	
	707.57												
64	706.64 -	63.5	150.0	6.5	4.76	6.35	10.0	M8	M8	5	1.0	75.0	
	707.64												

Materials

Couplers: Aluminium L168 or better

Fasteners: Alloy steel, black oiled

Temperature Range

-40°C to +120°C

- Length of supported bore.
- Max. compensation values are mutually exclusive.
- Peak torque.** Select a size where Peak Torque exceeds the application torque x service factor.
- 6-beam couplers only.** For applications where drive and driven shafts have minimal end-clearance, *relieved* version must be specified.

SERVICE FACTORS

Nature of load	Factor
Uni-directional - steady load	1
Uni-directional - stop/start	1.5
Reversing load	2

Coupler Type & Size	Set Screw Style	Clamp Style	ØD	L	L1	Bore Diameters			Set Screw	Cap Screw	Angular Offset Deg.	Parallel Offset mm	Peak Torque Nm
						Min B1	Min B2	Max B1 & B2					
Relieved	09	726.09 -	9.5	19.6	5.3	2.0	3.0	4.76	M2.5	M1.6	3	0.12	0.6
	13	726.13 -	12.7	22.9	6.5	3.0	4.0	6.35	M3	M2	5	0.17	1.3
		727.09 727.13											
	16	726.16 -	15.9	25.4	6.5	3.0	4.0	8.0	M4	M2.5	5	0.2	2.0
		727.16											
	19	726.19 -	19.1	26.5	6.5	4.76	5.0	10.0	M4	M2.5	5	0.25	3.0
		727.19											
	25	726.25 -	25.4	38.1	6.5	4.76	6.0	12.7	M5	M3	5	0.38	5.0
		727.25											
	32	726.32 -	31.8	57.2	6.5	4.76	6.35	19.0	M6	M4	5	0.5	7.0
		727.32											
	38	726.38 -	38.1	66.7	6.5	4.76	6.35	22.0	M6	M5	5	0.6	11.0
		727.38											
	44	726.44 -	44.5	76.2	6.5	4.76	6.35	25.0	M6	M5	5	0.8	15.0
		727.44											
	51	726.51 -	50.8	95.3	6.5	4.76	6.35	28.0	M8	M6	5	0.9	20.0
727.51													
57	726.57 -	57.2	130.0	6.5	4.76	6.35	32.0	M8	M6	5	0.95	28.0	
	727.57												
64	726.64 -	63.5	150.0	6.5	4.76	6.35	38.0	M8	M8	5	1.0	38.0	
	727.64												

If either shaft extends beneath the beams, the area shown in red must be **relieved** to provide clearance under the flexure.

HOW TO ORDER

Combine the COUPLER REF in Dimensions & Order Codes Table with BORE REFS in Bore Sizes Table. Please identify both bores e.g.

706.19.1924

Coupler ref.

Ø B1 ref.

Ø B2 ref.

BORE SIZES

NON-RELIEVED

RELIEVED

Coupler Size	ØB1, ØB2 +0.03/-0mm															
	2	3	3.175	4	4.763	5	6	6.350	8	9.525	10	12	12.700	14	15.875	16
09	○	○	○	●	●											
13		○	○	○	○	●	●	●								
16		○	○	○	○	○	●	●	●							
19				○	○	○	○	○	○	○	○	○	○	○	○	○
25					○	○	○	○	○	○	○	○	○	○	○	○
32								○	○	○	○	○	○	○	○	○

Coupler Size	ØB1, ØB2 +0.03/-0mm															
	2	3	3.175	4	4.763	5	6	6.350	8	9.525	10	12	12.700	14	15.875	16
09	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
13		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
16		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
19				○	○	○	○	○	○	○	○	○	○	○	○	○
25					○	○	○	○	○	○	○	○	○	○	○	○
32								○	○	○	○	○	○	○	○	○

Sizes 38 - 64 Manufactured to order only. Please enquire.

Sizes 38 - 64 Manufactured to order only. Please enquire.

Bore ref.	11	14	16	18	19	20	22	24	28	31	32	35	36	38	41	42
-----------	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Bore ref.	11	14	16	18	19	20	22	24	28	31	32	35	36	38	41	42
-----------	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

○ B1 only ● B1 & B2