Power Supplies Bench









Specification Table

Description	72-8350A	72-8345A	72-8340A
Input Voltage (Jumper Selection)	90-130 / 180-264V AC , 50/60Hz~		
Full Load Input Current at 230V AC	0.83A		
Output Voltage Adjustable Range	1 to 20V DC	1 to 36V DC	1 to 60V DC
Output Current Adjustable Range	0 to 5A	0 to 3A	0 to 1.6A

Voltage Regulation

Load from 10% to 100% Variation	120mV	50mV	50mV
Line from 180 to 264V AC Variation		20mV	
Ripple & Noise in r.m.s.	5mV	5mV	8mV
Ripple & Noise (peak to peak)	30mV	50mV	100mV

Current Regulation

Load from 10% to 100% Variation	20mA		
Line from 180 to 264V AC Variation	20mA		
Ripple & Noise (peak to peak)	70mA	20mA	20mA
Switching Operation Frequency	80KHz to 120KHz		
Power Factor	0.65		
Efficiency at Maximum Power	84%	83%	81%
Volt and Amp Control Type	Rotary Encoder		
Voltmeter and Ammeter Display	4 Digit		
Voltmeter Accuracy	±0.5% +5counts for range V≤5V	±0.5% +5counts for range V≤10V	±0.5% +5counts for range V≤20V
	±0.5% +3counts for range V>5V	±0.5% +3counts for range V>10V	±0.5% +3counts for range V>20V
Ammeter Accuracy	±0.5% +5counts for range I≤2A	±0.5% +5counts for range I≤1A	±0.5% +5counts for range I≤0.5A
	±0.5% +3counts for range I>2A	±0.5% +3counts for range I>1A	±0.5% +3counts for range I>0.5A
LCD Indication	CC, CV, Amp, Volt, Output ON-OFF		
Protection	Short Circuit, Overload, Over Temperature, Tracking OVP		
CE Approvals	LVD : EN 61010 , EMC : EN 55011		
Cooling System	Natural Convection		
Dimensions in mm (W×H×D)	70 × 150 × 250mm / 2.8 × 6.0 × 9.8in.		
Weight in Kg	2Kgs / 4.4Lbs		
Remarks	All the data are based on 230V 50Hz~		



Power Supplies Bench



Part Number Table

Description	Part Number	
PSU, DC, PROG, 60V, 1.6A	72-8340A	
PSU, DC, PROG, 36V, 3A	72-8345A	
PSU, DC, PROG, 20V, 5A	72-8350A	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.



