


VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

NOTES

- 1) 23 AWG, 4 CONDUCTOR WITH 21 STRANDS OF 36AWG TINNED COPPER.
- 2) CONDUCTORS: RUBBER INSULATED
- 3) CONDUCTOR COLOR CODE: BLACK, WHITE, GREEN, AND RED.
- 4) JACKET INSULATION TO BE NEOPRENE.
- 5) CORDAGE D.D.: .250" NDM.
- 6) APPROVALS: NONE
- 7) RATING: 60°C / 300 VOLTS MAX.
- 8) PACKAGING: 50 CORDS/CARTON
- 9) ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED.

 CUD	<input checked="" type="checkbox"/> Indianapolis, IN <input type="checkbox"/> Conover, N.C. <input type="checkbox"/> Freemont, CA <input type="checkbox"/> Aguascalientes, MX <input type="checkbox"/> Tijuana, Mexico <input type="checkbox"/> Hermosillo, MX <input type="checkbox"/> Clinton, AR <input type="checkbox"/> Kanata, Canada	<p>Proprietary Notice:</p> <p>This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.</p>	<p>MUST BE RQHS COMPLIANT</p> <p>FINISH: JACKET: SMOOTH</p>
--	--	---	---

REV	1	CUD - NEW RELEASE	ECD:	N/A	DATE	9/6/07
SCALE:	NDT TO SCALE					
TOLERANCE UNLESS OTHERWISE SPECIFIED						
.XXX ± .005						
.XX ± .02						
.X ± .03						
FRACT. ± 1/32°						
ANGULAR ± 1/2°						
ITEM DESCRIPTION		RETRACTILE CORD - NORTH AMERICAN				
APPROVED	DRAWN BY	DATE:				
STC	STC	9/6/07				
PART NO.		7415				