

## Traffic Control Signs (Continued)



75137 14" x 20" B-120  
25868 10" x 14" B-401  
43445 10" x 14" B-555



69562 7" x 17" B-120



129545 7" x 10" B-302  
129548 10" x 14" B-302  
129544 7" x 10" B-401  
129547 10" x 14" B-401  
129543 7" x 10" B-555  
129546 10" x 14" B-555



129551 7" x 10" B-302  
129554 10" x 14" B-302  
129550 7" x 10" B-401  
129553 10" x 14" B-401  
129549 7" x 10" B-555  
129552 10" x 14" B-555




129557 7" x 10" B-302  
129560 10" x 14" B-302  
129556 7" x 10" B-401  
129559 10" x 14" B-401  
129555 7" x 10" B-555  
129558 10" x 14" B-555




45474 14" x 20" B-120  
25874 10" x 14" B-401  
43451 10" x 14" B-555



80055 9" x 12" B-959



75063 5" x 14" B-120




80060 9" x 12" B-959



80101 24" x 6" B-959  
80103 24" x 6" B-959  
80102 36" x 12" B-959  
80104 36" x 12" B-959



94234 24" x 24" B-959  
94235 30" x 30" B-959



80061 9" x 12" B-959



94163 24" x 24" B-959



75066 24" x 24" B-120



132055 7" x 10" B-120  
132056 10" x 14" B-120  
132053 7" x 10" B-302  
132054 10" x 14" B-302  
132051 7" x 10" B-401  
132052 10" x 14" B-401  
132049 7" x 10" B-555  
132050 10" x 14" B-555



94307 30" x 30" B-959



80070 30" x 30" B-959  
80068 24" x 24" B-995  
80067 30" x 30" B-995



94222 24" x 24" B-959



### OSHA Requirements

#### Notice: Chock Rear Wheels 1910.178(k) and (m)

When trucks are loaded and unloaded, OSHA requires the brakes to be set and wheel chocks to be placed under the rear wheels to prevent the trucks from rolling while they are boarded with a forklift or other powered industrial truck.