Honeywell

Honeywell Sensing and Control

Home> Products > Conductive Plastic> MKII> Product Page

- Order Product and Get Support
- U.S. Authorized
 Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback



MKII Series Precision Potentiometer, Conductive Plastic Element, Turret Terminals, 1 W Power Rating, 10 kOhm Resistance Value

Actual product appearance may vary.

Features

Linearity (Accuracy) 0.5 % or less 10 Million to 20 Million Lifecycles Servo and Bushing Mounting Custom Electrical Travels

Description

Potential Applications

Valve Position Feedback Panel Control Instrumentation Missile Fin Position Feedback

Honeywell? s MKV and MKII Potentiometers offer a cost effective way of obtaining high accuracy, long life position feedback. Honeywell has many years of experience in successfully providing high reliability/high performance products to the military and aerospace industries and continues to expand that technical capability to the low cost/high performance industrial and commercial segments.

Supporting Documentation Dimensions

Product Specifications	
Potentiometer Type	Precision
Element Type	Conductive Plastic
Terminal Type	Turret
Power Rating	1 W
Resistance Value	10 kOhm
Resistance Tolerance	± 10 %
Linearity	± 0.5 %
Shaft Diameter	3,18 mm [0.125 in]
Shaft length	15,88 mm [0.625 in]
Shaft Ending	Plain round
Body	22,23 mm [0.875 in} diameter, ± 22,86 mm [0.900]
Electrical Taper	Linear
Operating Temperature	- 65 °C to 125 °C [- 85 °F to 257 ° F]
Working Voltage (Max.)	750 V
Rotational Life	30 million cycles
Mechanical Rotation	360°
Availability	Global
Series Name	МКІІ
UNSPSC Code	4111363327
UNSPSC Commodity	4111363300 Potentiometers

