

Product Specification

Daylite



Bulkhead
STXXW3LS1

STXXW3LS1

LED 2W M3 DAYLITE WHT/OPL SLFTST

Catalogue Number	STXXW3LS1
Category	Combined Escape route or Sign Luminaire
GTIN	05415022465983
GID	7TCA091160R0574
Warranty (Year)	3
Other	Refer to ABB warranty terms & conditions



Exit Sign
STXXW3LS1 + RSEN5X

Power Supply System	Self-Contained (individual battery)
Mounting Method	Ceiling, Wall
Mounting Form	Surface
Material Housing	Plastic
Colour Housing	White
Material Cover	Plastic, Opal
Material	Polycarbonate
Colour	White
Length (mm)	342
Width (mm)	98
Height/depth (mm)	72
Nominal Voltage (V)	220-240
Voltage Type	AC 50/60Hz
Duration (hours)	3
Battery	NiCd
Monitoring Equipment	Automatic self test
Lamp Type	LED
Lamp Power	2
Number of Lamps	1
Light output in Emergency Operation (lm)	214
Average Lifespan light source (hours)	100000
Colour of Light	White
Colour Temperature (K)	4000
CRI	80
Degree of Protection (IP)	65
Impact Strength (IK)	10
Wiring System	Maintained / non-maintained circuit
Type of Legend	Single Sided

Legend style	Self Adhesive Sticker
Recognition distance (m)	23
Power Consumption Maintained mode (W)	3.9
Power Consumption Maintained mode (VA)	6.1
Nominal current (mA)	25.5
Inrush Current (A to 0.1ms)	0.7
Power Factor	0.48
Temperature range (°C)	0 to 30°C
Weight (Kg)	0.75
Packaging	Cardboard box
Packaging dimensions (LxWxH) (mm)	365*107*86

Accessories

RSEN2X Down ISO7010 Legend

RSEN3X Left ISO7010 Legend

RSEN6X Right ISO7010 Legend

RSEN5X Up ISO7010 Legend

RSB1X Arabic English Legend

XTR Semi-recessing bezel White