



Fuse terminals

ASK 1¹⁾ ASK 1/35¹⁾



Dimensions/approvals	
Width/length/height (mm)	with TS 32 8/58/45.5
Width/length/height (mm)	with TS 35 x 7.5 8/58/44
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/6.3 A ²⁾ /4 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 0.5...1.0
Torque setting with electric screwdriver type DMS 2	2
Clampable conductor	
Solid H07V-U	mm ² 0.5...4
Stranded H07V-R	mm ² 1.5...4
Flexible H07V-K	mm ² 0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...4
Plug gauge according to 60 947-7-1	Size A 3
Continuous current rating of cross-connection 2...5-pole	A (QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole	A

KDKS 1¹⁾ KDKS 1/35¹⁾




Dimensions/approvals	
Width/length/height (mm)	8/73.5/59.8
Width/length/height (mm)	8/73.5/55.7
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/6.3 A/4 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 0.5...1.0
Torque setting with electric screwdriver type DMS 2	2
Clampable conductor	
Solid H07V-U	mm ² 0.5...4
Stranded H07V-R	mm ² 1.5...4
Flexible H07V-K	mm ² 0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...4
Plug gauge according to 60 947-7-1	Size A 4
Continuous current rating of cross-connection 2...5-pole	(QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole	

SAKS 1 SAKS 1/35



Dimensions/approvals	
Width/length/height (mm)	13/54/61
Width/length/height (mm)	13/54/54
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1.0
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/6.3 A ³⁾ /10 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4
Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	(QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	(QL 6...10) 36

SAKS 1/G25 SAKS 1/35/G25



Dimensions/approvals	
Width/length/height (mm)	13/54/61
Width/length/height (mm)	13/54/54
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1.0
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/6.3 A ³⁾ /10 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4
Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	(QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	(QL 6...10) 36

Dimensions/approvals	
Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	
Rated impulse voltage/pollution severity	
Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	
Clampable conductor	
Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/6.3 A/12 max. AWG
Voltage/current/conductor size	CSA 300 V/6.3 A/26...12 AWG
Ordering data	Version Qty. Qty.
	PA 0474560000 100
	KrG 9503300000 50 9503310000 50
	Beige Wemid 0191220000 20 0501620000 20

End plate/partition (thickness mm)	
	Type AP (1.5) Cat. No. 0380360000 Qty. 20
	Type AP (2.5) Cat. No. 0191320000 Qty. 20
	Wemid 9532470000 25
	for TW (2.0) 0607000000 20

G-fuse inserts	
Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1) rated current (A):	0.10 fast 0430300000 10
Rated voltage 250 V	0.20 fast 0430400000 10
Fast switching capacity 1500 A	0.25 fast 0430500000 10
(at 250 V, 50 Hz, cos φ = 0.7)	0.50 fast 0430600000 10
	1.0 fast 0430700000 10
	1.6 fast 0430800000 10
	2.0 fast 0430900000 10
	2.5 fast 0431000000 10
	3.15 fast
	4.0 fast
	5.0 fast
	6.3 fast

	Contact sleeve 0553300000 100
	Screw cap/disconnector lever (spare)
	TH 0377060000 100
	SIHA 1593020000 100
	Red pull lever

Marking tags	
	DEK Standard DEK 8 see "Accessories"
	DEK 8 see "Accessories"
	DEK 5 see "Accessories"
	DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ Multipole interruptable with group marking carrier
Sch2 2-pole Cat. No. **1359500000**, 1000 mm Cat. No. **0337400000**

Fuse terminals

**SAKS 3
SAKS 3/35**



**SAKS 4
SAKS 4/35**



**SAKS 5
SAKS 5/35**



**SAKS 2
SAKS 2/35**



Dimensions/approvals	
Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data/feed through-terminal base	
Rated voltage/current/cross-section	
Rated impulse voltage/pollution severity	

Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm²
Stranded H07V-R	mm²
Flexible H07V-K	mm²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²
Plug gauge according to 60 947-7-1	Size
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data	
Version	
KrG	
KrG	

End plate/partition (thickness mm)	
PA	
HP	



Fuse inserts	
1 1/4" x 1/4"	Nominal current (A): 0.5 fast
	1.0 fast
	2.0 fast
	3.0 fast
	5.0 fast
	7.0 fast
	10.0 fast

E 0.5 A	0533800000
E 1 A	0525500000
E 2 A	0294500000
E 3 A	0295700000
E 5 A	0294600000
E 7 A	0295800000
E 10 A	0293900000

G fuse inserts 5 x 30 mm
(500 V - /0.032...6.3 A).
Available from Wickmann-Werke GmbH,
Annastr. 113, 58453 Witten, Germany, Phone ++492302/6620

D fuse inserts	
Rated voltage 400 V	
E 14/2	0137400000 10
E 14/4	0137500000 10
E 14/6	0328300000 10
E 14/10	0328400000 10
E 14/16	0328500000 10

Screw cap (spare)	
red	SK (5 x 30) 0282000000 20
black	SK (1/4"x1 1/4") 0428900000 20

Marking tags	
	DEK Standard

Mounting rails, end brackets, further marking material see "Accessories"

	13/54/61
	13/54/55
	12 mm/M 4/5.5 x 1
	500 V/10 A/10 mm²
	6 kV/3
	1.2...2.4
	4
	0.5...16
	1.5...10
	0.5...10
	0.5...10
	B 6
	(QL 2...5) 47
	(QL 6...10) 36

	24/75/73
	24/75/66
	14 mm/M 4/5.5 x 1
	400 V**/16 A/10 mm²
	6 kV/3
	1.2...2.4
	4
	0.5...16
	1.5...10
	0.5...10
	0.5...10
	B 6
	(QL 2...5) 47
	(QL 6...10) 36

	28/80/80.5
	28/80/66
	13 mm/M 4/5.5 x 1
	400 V/63 A***/16 mm²
	6 kV/3
	1.2...2.4
	4
	1.5...16
	1.5...16
	1.5...16
	1.5...16
	B 7
	(QL 2...5) 47
	(QL 6...10) 36

	28/80/81.5
	28/80/75
	12 mm/M 4/5.5 x 1
	500 V/10 (25) A***/10 mm²
	6 kV/3
	1.2...2.4
	4
	0.5...16
	0.5...10
	0.5...10
	0.5...10
	B 6
	(QL 2...5) 47
	(QL 6...10) 36

Ordering data	
Version	
KrG	
KrG	
Neozed D 01	
Type	Cat. No. Qty.
TW HP (2.0)	0607000000* 20
QL 2 0328000000 20	
QL 3 0328100000 20	
QL 4 0328200000 20	
QL 10 0339000000 20	
SS M 4 0136400000 100	
BS M 4x9 0103300000 100	
Gauge ring	
Amp. Colour	Cat. No. Qty.
P 14/2 pink	0138000000 50
P 14/4 brown	0138100000 50
P 14/6 green	0328600000 50
P 14/10 red	0328700000 50

Ordering data	
Version	
KrG	
KrG	
Neozed D 02	
Type	Cat. No. Qty.
TW HP (2.0)	0607000000* 20
QL 2 0207800000 20	
QL 3 0207900000 20	
QL 4 0208000000 20	
QL 10 0338900000 20	
SS M 4 0136400000 100	
BS M 4x9 0103300000 100	
Gauge ring	
Amp. Colour	Cat. No. Qty.
P 18/20 Blue	0361800000 50
P 18/25 yellow	0361900000 50
P 18/35 black	0362000000 50
P 18/50 white	0362100000 50

Ordering data	
Version	
KrG	
KrG	
Diazed E 16	
Type	Cat. No. Qty.
TW HP (2.0)	0607000000* 20
QL 2 0207800000 20	
QL 3 0207900000 20	
QL 4 0208000000 20	
QL 10 0338900000 20	
SS M 4 0136400000 100	
BS M 4x9 0103300000 100	
Gauge ring	
Amp. Colour	Cat. No. Qty.
P 16/10 red	0208900000 100
P 16/16 grey	0209000000 100
P 16/20 Blue	0209100000 100

Gauge ring	
Rated voltage 400 V	
E 18/20	0361300000 10
E 18/25	0361400000 10
E 18/35	0361500000 10
E 18/50	0361600000 10
E 18/63	0361700000 10

Gauge ring	
Rated voltage 400 V	
E 10 A	0208500000 25
E 16 A	0208600000 25
E 20 A	0208700000 25
E 25 A	0208800000 25

Gauge ring	
Rated voltage 500 V	

*only for TS 32

** Also for 440 V - with neozed marina fuse
*** Current for overload up to 10 A, for short circuit up to 25 A

3) For fuse inserts 1 1/4 x 1/4 DEF 63
4) For fuse inserts 5 x 30

Fuse terminals

SAKS 4 USA




UL
24/75/73
24/75/66
14 mm/M 4/5.5 x 1
400 V/30 A/10 mm ²
6 kV/3
1.2...2.4
4
0.5...16
1.5...10
0.5...10
0.5...10
B 6
(QL 2...5) 47
(QL 6...10) 36
600 V/30 A/20...8 AWG
600 V/30 A/22...8 AWG
Qty. Qty.
0162220000 20 0178220000 20
10.3 x 38,1
Type Cat. No. Qty.
TW HP (2.0) 0607000000* 20
QL 2 0328000000 20
QL 3 0328100000 20
QL 4 0328200000 20
QL 10 0339000000 20
SS M 4 0136400000 100
BS M 4 x 9 0103300000 100
SK (w. spring) 0161730000 20
DEK 5 see "Accessories"

Fuse terminals with fault indicator



Dimensions/approvals
Terminal width (+ 0.2 assembly tolerance) mm
Insulation stripping length mm
Connection data
Screw connection, solid
Screw connection, flexible/ferrule with/without plastic collar
Conductor cross-section
VDE rated data
Current
Voltage
LED-current (24...60 V)
LED-current (115...230 V)
LED-current (24...230 V)
Incandescent lamp-current
Neon lamp-current
Cross-section
Ordering data
24 V- ASK 1 LD 8050810000 25
24 V- ASK 1 LD 0222760000 25
48 V- ASK 1 LD 0225260000 25
60 V- ASK 1 LD 0226460000 25
115 V- ASK 1 LD 0225460000 25
230 V- ASK 1 LD 0225660000 25
24 V- ASK 1 LD 0222860000 25
48 V- ASK 1 LD 0225360000 25
60 V- ASK 1 LD 0226360000 25
115 V- ASK 1 LD 0225560000 25
230 V- ASK 1 LD 0225760000 25
Mountable on TS 32 and TS 35
TS 32 0122800000
TS 35x7.5 0383400000
TS 35x15 0498000000
EWK 1 0206160000 50
EW 35 0383560000 50
AP PA (1.5) 0380360000 20
QB 2 ¹⁾ 0461100000 100
QB 3 ¹⁾ 0461200000 50
QB 4 ¹⁾ 0461300000 50
straight QB 58 ¹⁾ 0545400000
angled QB 58 ¹⁾ 0545300000
Fixing screw (fits QL)
Disconnect lever (spare) TH (spare) 0377060000 100
Accessories
Mounting rail
End brackets (thickness mm) for TS 32
for TS 35
End plate/End plate (thickness mm)
Cross-connections
Type 'QL'
Cross-connection
Type 'QB'
Fixing screw (fits QL)
Disconnect lever (spare)
Mounting rails, end brackets, further marking material see "Accessories"

ASK 1 LD




Warning:
In the event of a faulty fuse, the connection system is live!

UL
8
9
0.5...4 mm ²
0.5...4 mm ²
AWG 22...12
6.3 A
24...230 V (depending on terminal)
≤ 2 mA
≤ 2 mA
4 mm ²
Type Cat. No. Qty.
ASK 1 LD 8050810000 25
ASK 1 LD 0222760000 25
ASK 1 LD 0225260000 25
ASK 1 LD 0226460000 25
ASK 1 LD 0225460000 25
ASK 1 LD 0225660000 25
ASK 1 LD 0222860000 25
ASK 1 LD 0225360000 25
ASK 1 LD 0226360000 25
ASK 1 LD 0225560000 25
ASK 1 LD 0225760000 25
Mountable on TS 32 and TS 35
TS 32 0122800000
TS 35x7.5 0383400000
TS 35x15 0498000000
EWK 1 0206160000 50
EW 35 0383560000 50
AP PA (1.5) 0380360000 20
QB 2 ¹⁾ 0461100000 100
QB 3 ¹⁾ 0461200000 50
QB 4 ¹⁾ 0461300000 50
straight QB 58 ¹⁾ 0545400000
angled QB 58 ¹⁾ 0545300000
Fixing screw (fits QL)
Disconnect lever (spare) TH (spare) 0377060000 100

KDKS 1

Fuse insert 5 x 20



Warning:
In the event of a faulty fuse, the connection system is live!

8
9
0.5...4 mm ²
0.5...4 mm ²
AWG 22...12
6.3 A
24...230 V (depending on terminal)
≤ 2 mA
4 mm ²
Type Cat. No. Qty.
KDKS 1 8146450000 25
KDKS 1 8148930000 25
KDKS 1 8148920000 25
KDKS 1 8142840000 25
KDKS 1 8148910000 25
Mountable on TS 32 and TS 35
TS 32 0122800000
TS 35x7.5 0383400000
TS 35x15 0498000000
EWK 1 0206160000 50
EW 35 0383560000 50
AP PA (1.5) 0380360000 20
QB 2 ¹⁾ 0461100000 100
QB 3 ¹⁾ 0461200000 50
QB 4 ¹⁾ 0461300000 50
straight QB 58 ¹⁾ 0545400000
angled QB 58 ¹⁾ 0545300000
Fixing screw (fits QL)
Disconnect lever (spare) TH (spare) 0377060000 100

SAK-series

¹⁾When using QB, the rated cross-current reduces to max. 2.5 mm²


Fuse terminals

with fault indicator



SAKS 1


Fuse insert 5 x 20/5 x 25



Warning:
In the event of a faulty fuse, the connection system is live!

SAKS 4


Fuse insert E14/D 01
(e.g. Neozed D 01)



Warning:
In the event of a faulty fuse, the connection system is live!

SAKS 6


Fuse insert 1 1/4" x 1/4" acc. to DEF 63



Warning:
In the event of a faulty fuse, the connection system is live!

SAKS 7

Fuse insert 5 x 20/5 x 25



Warning:
In the event of a faulty fuse, the connection system is live!

Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length/clamping screw/screwdriver blade	

Connection data

Screw connection, solid	
Screw connection, flexible	
Conductor cross-section	

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

VDE rated data

Voltage/current	-/10 A
LED-current (24...60 V)	≤ 5 mA
LED-current (115...230 V)	
Incandescent lamp-current	≤ 50 mA
Neon lamp-current	≤ 0.5 mA
Cross-section	10 mm ²

Ordering data

	Voltage	Qty.
Fuse insert		
5 x 20	LED	24 V~
Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1)		24 V~
without indicator		48 V~
		48 V~
	Incandescent lamp	24 V~
		48 V~
	Neon lamp	115 V~
		230 V~
Fuse insert		
5 x 25	LED	24 V~
Acc. to DIN 41576		
without indicator		48 V~
	Incandescent lamp	48 V~
	Neon lamp	115 V~
		230 V~

Accessories

Mounting rail	
End brackets (thickness mm)	for TS 32
	for TS 35
End plate (thickness mm)	
Cross-connection	
Type 'QL'	
Cross-connection	
Type 'QB'	
Fixing screw (fits QL)	
Screw cap (spare)	
Neon lamp	

UL

13
12
0.5...16 mm ²
0.5...10 mm ²
AWG 20...8

UL

24
14
0.5...16 mm ²
0.5...10 mm ²
AWG 20...7

UL

12
12
0.5...16 mm ²
0.5...10 mm ²
AWG 20...8

UL

12
12
0.5...16 mm ²
0.5...10 mm ²
AWG 20...8

Type	Cat. No.	Qty.
SAKS 1 LD		
	0371420000	10
	0225820000	10
	1111220000	10
	1111320000	10
	0214020000	10
SAKS 1 GL		
	0173220000	10
	0378920000	10
SAKS 1 GL		
	0385320000	10
	8068330000	10
	0306120000	10
	0199920000	10
SAK 1 LD		
	on demand	
SAKS GL		
	on demand	
SAKS 1 GL		
	0309320000	10
	0198620000	10

Type	Cat. No.	Qty.
SAKS 4		
TS 32 Neon lamp		
Voltage		
115 V~	0101820000	10
480 V~	0102120000	10

Type	Cat. No.	Qty.
SAKS 6 KrG	0531820000	40
for 1 1/4" x 1/4" acc. to DEF 63		
exchangable neon lamps (please order separately)		

Type	Cat. No.	Qty.
SAKS 7 KrG		
for 5 x 25	0576120000	40
SAKS 7 KrG		
for 5 x 20	0573120000	40
exchangable neon lamps (please order separately)		

Type	Cat. No.	Qty.
TS 32	0122800000	
TS 35x7.5	0383400000	
TS 35x15	0498000000	
EWK 1 (8.5)	0206160000	50
EW 35 (8.5)	0383560000	50
AP KrG (3)	0191320000	20
SK (5 x 20)	0282100000	20
SK (5 x 25)	0282000000	100

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50
AP KrG	0146720000	20
QL 2	0191400000	50
QL 3	0191500000	50
QL 4	0191600000	20
QL 10	0338800000	20
BSM 3x6 m.SS	0346200000	100
Neon lamp 230 V~	0550300000	
Neon lamp 115 V~	0550200000	

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50
AP KrG (3)	0146720000	20
QL 2	0207800000	20
QL 3	0207900000	20
QL 4	0208000000	20
QL 10	0338900000	20
BSM 4x9 m.SS	0133300000	100
Neon lamp 230 V~	0550300000	
Neon lamp 115 V~	0550200000	

Fuse inserts and gauge rings for Weidmüller fuse terminals




Fuse inserts

for terminal type	Size (mm)	Rated voltage (V)	Rated current (A)	Type	Cat. No.	Qty.
G fuse inserts 5 x 20 without indicator acc. to IEC 60127-2 (VDE 0820 T.2 Bl 1)						
SAKS 1	5 x 20 Breaking capacity 1500 A (at 250 V, 50 Hz, cos φ 0.7)	250	0.1 (F)	G 20/0.10A/F	0430300000	10
SAKS 7			0.2 (F)	G 20/0.20A/F	0430400000	10
ASK 1			0.25 (F)	G 20/0.25A/F	0430500000	10
WSI 6 			0.5 (F)	G 20/0.50A/F	0430600000	10
			0.63 (F)	G 20/0.63A/F	0439000000	10
			1.0 (F)	G 20/1.00A/F	0430700000	10
			1.6 (F)	G 20/1.60A/F	0430800000	10
			2.0 (F)	G 20/2.00A/F	0430900000	10
			2.5 (F)	G 20/2.50A/F	0431000000	10
			3.15 (F)	G 20/3.15A/F	0431100000	10
			4.0 (F)	G 20/4.00A/F	0431200000	10
			5.0 (F)	G 20/5.00A/F	0431300000	10
			6.3 (F)	G 20/6.30A/F	0431400000	10
G fuse inserts 5 x 25 with indicator acc. to DIN 41576¹⁾						
SAKS 1	5 x 25 m. K.1) Breaking capacity 80 A (at 250 V, 50 Hz, cos φ = 1)	250	0.25 (M)	G 25/0.25A/M	0546900000	10
SAKS 7			0.5 (M)	G 25/0.50A/M	0510300000	10
WSI 6 			0.8 (M)	G 25/0.80A/M	0646400000	10
			1 (M)	G 25/1.00A/M	0265800000	10
			10 (M) ²⁾	G 25/10.0A/M	0193100000	10
			2 (F)	G 25/2.00A/F	0192700000	10
			4 (F)	G 25/4.00A/F	0192800000	10
			6.3 (F)	G 25/6.30A/F	0192900000	10
			Fuse inserts 1 1/4" x 1/4" without indicator acc. to BS 88			
SAKS 3 ²⁾	33 kA Breaking capacity 33 kA fast	440	E 0.5 A	GZ 0.5A/F	0533800000	10
SAKS 6 			E 1 A	GZ 1.0A/F	0525500000	10
			E 2 A	GZ 2.0A	0294500000	10
			E 3 A	GZ 3.0A	0295700000	10
			E 5 A	GZ 5.0A	0294600000	10
			E 7 A	GZ 7.0A	0295800000	10
			E 10 A	GZ 10.0A	0293900000	10
D fuse inserts E 16 with indicator acc. to DIN 49360 (diazed)						
SAKS 2 	E 10 A E 16 A E 20 A E 25 A	500	10	E 16/10A RT	0208500000	25
			16	E 16/16A GR	0208600000	25
			20	E 16/20A BL	0208700000	25
			25	E 16/25A GE	0208800000	25
D fuse inserts E 14 Size D 01 and E 18 size D 02 with indicator acc. to DIN 49522 (neozed)³⁾						
SAKS 4 ⁴⁾ 	E 14/2 E 14/4 E 14/6 E 14/10 E 14/16 E 18/20 E 18/25 E 18/35 E 18/50 E 18/63	400	2	E 14/2A RS	0137400000	10
			4	E 14/4A BR	0137500000	10
			6	E 14/6A GN	0328300000	10
			10	E 14/10A RT	0328400000	10
			16	E 14/16A GR	0328500000	10
			20	E 18/20A BL	0361300000	10
			25	E 18/25A GE	0361400000	10
			35	E 18/35A SW	0361500000	10
SAKS 5 	E 18/50 E 18/63	400	50	E 18/50A WS	0361600000	10
			63	E 18/63A KU	0361700000	10

(F) = fast
(M) = medium-delayed action

- Note:**
- 1) The SIBA company also supplies 5 x 25 G fuse inserts with indicators in a shipbuilding model for 450 V AC.
 - 2) 5 x 30 (500 V AC) fuse inserts for SAKS 3 are available from the WICKMANN company
 - 3) The LINDNER company also supplies neozed fuse cartridges in an additional shipbuilding mode for 440 V AC.
 - 4) Fuse cartridges with the dimensions 1"x1/4" ≙ 25.4x6.35 mm and 13/32"x1 1/2" ≙ 10.3x38.1 mm are not included in product line.
 - 5) Only for SAKS 1 and SAKS 7.

Gauge rings

For terminal type	Gauge ring type	Amp.	Colour	Type	Cat. No.	Qty.
SAKS 4 and 4/35 	P 14/2	2	Pink	P 14/2D01 RS	0138000000	50
	P 14/4	4	Brown	P 14/4D01 BR	0138100000	50
	P 14/6	6	Green	P 14/6D01 GN	0328600000	50
	P 14/1	10	Red	P 14/10D01 RT	0328700000	50
SAKS 5 and 5/35 	P 18/20	20	Blue	P 18/20D02 BL	0361800000	50
	P 18/25	25	Yellow	P 18/25D02 GE	0361900000	50
	P 18/35	35	Black	P 18/35D02 SW	0362000000	50
	P 18/50	50	White	P 18/50D02 WS	0362100000	50
SAKS 2 and 2/35 	P 16/10	10	Red	P 16/10 RT	0208900000	100
	P 16/16	16	Grey	P 16/16 GR	0209000000	100
	P 16/20	20	Blue	P 16/20 BL	0209100000	100