



+ CONNECTORS

TRANSISTOR SOCKETS



✓ Active

TE CONNECTIVITY (TE)

8058-24G1=TO5 SOCKET 230 CIRC

Augat | AD

8058-24G1

TE Internal Number: 3-1437508-2

[EU RoHS Compliant with Exemptions](#)

[EU ELV Compliant with Exemptions](#)

Number of Positions 10

Profile Low

Package TO-5

Lead Size Accepted .41 mm [.016 in]

Termination Method Printed Circuit

[↓](#) **PRODUCT DRAWING**
English

DOCUMENTATION

Product Drawings

SOCKET, 8 PIN PRINTED CIRCUIT

PDF (TIFF AVAILABLE)

English

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Terminal Configuration Contact
Profile Low
Package TO-5
Product Type Socket

Configuration Features

Number of Positions 10

Body Features

Lead Size Accepted .41 mm [.016 in]
Color Black
Insulator Material Fluoropolymer
Sleeve Plating Material Gold
Sleeve Material Brass

Contact Features

Terminal Plating Gold
Termination Method Printed Circuit
Pin Diameter 5.84 mm [.23 in]
Terminal Material Beryllium Copper
Socket Type Transistor

Usage Conditions

Operating Temperature Range (°C) -55 – 125

Industry Standards

Insulator Flammability Rating UL 94V-0

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
