




PRODUCT NUMBER: 807-22-001-30-000101

www.mill-max.com
DATA SHEET



807-22-001-30-000101- SPECIFICATIONS

General Info	
Description¹:	PCB Mount Spring-Loaded Header Initial Height .100" (2,540mm)
Type:	Spring-Loaded
Category:	Single Insulated Pogo Pin
Mounting Style:	Surface Mount
# Pins:	1
RoHS:	Yes
Product Lifecycle:	Active

Materials	
Shell Plating:	20μ" Gold over 100μ" Nickel
Inner Plating:	(Spring) 10μ" Gold
Loose Pin/Receptacle Used:	0965 (Brass Alloy)
Insulator Material:	Nylon 46

Technical Specs	
Initial Height:	.100" (2,540mm)
Rows:	Rows: Single Row (1)
A Dim:	.100" (2,540mm)
B Dim:	.024" (0,610mm)
C Dim:	.055" (1,397mm)

NOTES:

1. Standard Tolerances

Assembly tolerance: +/- .010" (.25mm)

Connector Length "L"

Connector Length "L"	Tolerance
$L \leq 2"$ ($L \leq 50.8$ mm)	+/- .005" (+/- .127 mm)
$2 < L \leq 3"$ ($50.8 < L \leq 76.2$ mm)	+ .007 / - .006" (+ .178 / - .152 mm)
$3 < L \leq 4"$ ($76.2 < L \leq 101.6$ mm)	+ .009 / - .007" (+ .229 / - .178 mm)
$4 < L \leq 5"$ ($101.6 < L \leq 127$ mm)	+ .011 / - .008" (+ .279 / - .203 mm)
$5 < L \leq 6.4"$ ($127 < L \leq 162.56$ mm)	+ .013 / - .009" (+ .330 / - .229 mm)

Insulator width: +/- .005 (.13mm)

Insulator height: +/- .005 (.13mm)

Co-planarity of SMT connectors: .005" (.13mm) up to 1" (25.4mm) in connector length

Insulator Flatness: .005" (.13mm) up to 1" (25.4mm) in connector length

Pin Length: +/- .006 (.15mm)

Pin Diameter: +/- .002 (.051mm)

Pin Angle: +/- 2°

ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.