

#### TRANSISTOR SOCKETS



✓ Active

## TE CONNECTIVITY (TE)

# 8080-1G14=TRANSISTOR SOCKET AS

Augat | AD

8080-1G14

TE Internal Number: 3-1437504-2

Not EU RoHS Compliant Not EU ELV Compliant

**Number of Positions** 3

Package TO-3

Lead Size Accepted 1.52 mm [.06 in]

**Termination Method** Solder

**Operating Temperature Range (°C)** -55 – 125



**PRODUCT DRAWING** 

English



**→** 3D PDF

## **DOCUMENTATION**

**Product Drawings** 

# TRANSISTOR SOCKET

PDF

**English** 

**CAD Files** 

# **Customer View Model**

2D\_DXF.ZIP

**English** 

#### **3D PDF**

PDF

3D

3D_IGS.ZIP  English	
Customer View Model 3D_STP.ZIP English	
FEATURES	+
Please review product documents or contact us for the latest agency approval information.	
Please Note: Use the Product Drawing for all design activity.	
Due duet Twee Feetunes	
Product Type Features  Terminal Configuration Contact	
Package TO-3	
Product Type Socket	
Configuration Features	
Number of Positions 3	
Number of Solder Lugs 1	
Body Features	
Lead Size Accepted 1.52 mm [.06 in]	
Color Green or Blue	
Insulator Material Phenolic	
Contact Features	
Terminal Plating Tin	
Termination Method Solder	
Pin Diameter (in) .04  Terminal Material Beryllium Copper	
Socket Type Transistor	
Usage Conditions	
Operating Temperature Range (°C) -55 – 125	
——————————————————————————————————————	
Industry Standards	
Insulator Flammability Rating UL 94V-0	
PRODUCT COMPLIANCE	+
Statement of Compliance	
Statement of Compliance	
Statement of Compliance PDF	

**Customer View Model**