

Crydom

See full Datasheet below...

onlinecomponents.com
THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS

BUY NOW

 **MASTER**TM
ELECTRONICS

BUY NOW

masterelectronics.com & onlinecomponents.com
are **authorized** e-commerce distributors
of electronic components.

Miniature solenoid valves for footprint CNOMO E 06-36-120N 3/2 NC Function impulse with manual override by impulse Part number 81519378




- Conform to the Low Voltage Directive
- For mounting on sub-base or footprint in accordance with CNOMO recommendation E 06-36-120N

Type	Consumption	Voltage
81519080 3/2 NC Function with Manual override	81 519 080.	24 V AC 50 - 60 Hz
81519380 3/2 NC Function impulse with manual override by impulse	81 519 380.	24 VAC 50 - 60 Hz
81519381 3/2 NC Function impulse with manual override by impulse	-	48 VAC 50 - 60 Hz
81519378 3/2 NC Function impulse with manual override by impulse	-	110 VAC 50 - 60 Hz
81519379 3/2 NC Function impulse with manual override by impulse	-	220 V - 230 V 50 - 60 Hz
81519680 3/2 NC with manual override by latching	81 519 680.	24 VAC 50 - 60 Hz
81519678 3/2 NC with manual override by latching	-	110 VAC 50 - 60 Hz
81519679 3/2 NC with manual override by latching	-	220 V - 230 VAC 50 - 60 Hz

Operating pressure (bar)


Orifice diameter mm	0,5
Flow at 6 bars NI/min	12
kV	0,12
Switching time (ms)	5 - 15
Mechanical life (operations)	5.10 ⁷
Operating temperature (°C)	-10+50
Permissible fluid: Compressed air or inert gas - oil-free air filtered to 50 <mu>	•
Operator factor	100% ED
Isolation class IEC 85	F
Weight (g)	35
Rotatable connector 4 positions in 90°	•
Degree of protection with sub-base	IP 20
Degree of protection with connector 81 516 082	IP 65
Approvals UL and cUL	MH 15085

Dimension Diagram : *** TRADUCTION MANQUANTE ***



N°	Legend
1	Manual override

Dimension Diagram : *** TRADUCTION MANQUANTE ***



N°	Legend	N°	Legend
1	2 x M3 - 6 H depth 6		

- 2 Solenoid valve projecting on this side
- 3 Adjacent side of footprint when valves mounted in bank
- 4 2 or 3 Ø 1,6 min 2 max
- 1
- 2
- 3