


**Miniature solenoid valves for footprint CNOMO E 06-36-120N 3/2 NC with manual override by latching Part number 81519678**


- Conform to the Low Voltage Directive
- For mounting on sub-base or footprint in accordance with CNOMO recommendation E 06-36-120N


	Type	Consumption	Voltage
81519080	3/2 NC Function with Manual override	81 519 080.	24 V AC 50 - 60 Hz
81519380	3/2 NC Function impulse with manual override by impulse	81 519 380.	24 VAC 50 - 60 Hz
81519381	3/2 NC Function impulse with manual override by impulse	-	48 VAC 50 - 60 Hz
81519378	3/2 NC Function impulse with manual override by impulse	-	110 VAC 50 - 60 Hz
81519379	3/2 NC Function impulse with manual override by impulse	-	220 V - 230 V 50 - 60 Hz
81519680	3/2 NC with manual override by latching	81 519 680.	24 VAC 50 - 60 Hz
81519678	3/2 NC with manual override by latching	-	110 VAC 50 - 60 Hz
81519679	3/2 NC with manual override by latching	-	220 V - 230 VAC 50 - 60 Hz

**Operating pressure (bar)**

Orifice diameter mm	0,5
Flow at 6 bars NI/min	12
kV	0,12
Switching time (ms)	5 • 15
Mechanical life (operations)	5.10 <sup>7</sup>
Operating temperature (°C)	-10+50
Permissible fluid: Compressed air or inert gas - oil-free air filtered to 50 <mu>	■
Operator factor	100% ED
Isolation class IEC 85	F
Weight (g)	35
Rotatable connector 4 positions in 90°	■
Degree of protection with sub-base	IP 20
Degree of protection with connector 81 516 082	IP 65
Approvals UL and cUL	MH 15085

**Dimension Diagram : \*\*\* TRADUCTION MANQUANTE \*\*\***


N°	Legend
1	Manual override

**Dimension Diagram : \*\*\* TRADUCTION MANQUANTE \*\*\***


N°	Legend	N°	Legend
1	2 x M3 6 H depth 6		
2	Solenoid valve projecting on this side		
3	Adjacent side of footprint when valves mounted in bank		

4 2 or 3 Ø 1,6 min 2 max

1

2

3