



Product: [83006](#)

Lead Wire, #22 Str SPC, TFE Ins, AWM 1213 105C TYPE E

[Request Sample](#)

Product Description

High Temp Plastic Lead Wire, 22AWG (19x34) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
22	19x34	SC - Silvered Copper	1

Conductor Count: 1

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PTFE - Polytetrafluoroethylene	0.048 in	0.009 in

Outer Jacket Material

Nominal Diameter
0.05 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
15.75 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Mil-Std-975M Table 3.16 (single wire)	4.5 Amps Single Wire (Mil-Std-975M Table 3.16)

Voltage

Description	Voltage Rating [V]
Mil-W-16878/4	600 V RMS Mil-W-16878/4

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

Bulk Cable Weight:	4 lbs/1000ft
--------------------	--------------

Standards

UL AWM Style Compliance:	1213
Military Compliance:	NEMA HP3, MIL-W-16878/4 (Except For Stranding)

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
83006 010100	Black	Reel	100 ft	
83006 010500	Black	Reel	500 ft	
83006 0101000	Black	Reel	1,000 ft	612825378365
83006 006500	Blue, Light			
83006 006100	Blue, Light	Reel	100 ft	
83006 0061000	Blue, Light	Reel	1,000 ft	612825399346
83006 001100	Brown	Reel	100 ft	
83006 001500	Brown	Reel	500 ft	
83006 0011000	Brown	Reel	1,000 ft	
83006 008100	Gray	Reel	100 ft	
83006 0081000	Gray	Reel	1,000 ft	612825399360
83006 005100	Green, Dark	Reel	100 ft	612825354437
83006 005500	Green, Dark	Reel	500 ft	
83006 0051000	Green, Dark	Reel	1,000 ft	612825399339
83006 0031000	Orange			
83006 003100	Orange	Reel	100 ft	
83006 002100	Red	Reel	100 ft	612825354420
83006 002500	Red	Reel	500 ft	
83006 0021000	Red	Reel	1,000 ft	612825378358
83006 007100	Violet			
83006 0071000	Violet	Reel	1,000 ft	612825399353
83006 009100	White	Reel	100 ft	
83006 009500	White	Reel	500 ft	
83006 0091000	White	Reel	1,000 ft	612825354048
83006 004100	Yellow	Reel	100 ft	
83006 004500	Yellow	Reel	500 ft	
83006 0041000	Yellow	Reel	1,000 ft	612825399322

Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.
Footnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)

History

Update and Revision:	Revision Number: 0.286 Revision Date: 06-08-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief

at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.