Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83008 Hook-up/Lead - UL AWM Style 1213

For more Information please call

1-800-Belden1



General Description:

.....

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

Physical Characteristics (Overall)	
Conductor	
AWG:	
# Conductors AWG Stranding Conductor Material 1 20 7x28 SPC - Silver Plated Co	
	pper
Total Number of Conductors:	1
Insulation Insulation Material:	
Insulation Material Wall Thickness (mm)	
TFE - Tetrafluoroethylene 0.254	
Overall Insulation Overall Cable	
Overall Nominal Diameter:	1.473 mm
Applicable Specifications and Agency Co	
Applicable Specifications and Agency Co Applicable Standards & Environmental Progr	• • •
UL Rating:	105°C
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	NEMA HP3, MIL-W-16878/4
MIL Spec Rating:	600 V, 200°C
Flame Test	
UL Flame Test:	VW-1
Plenum/Non-Plenum	
Plenum (Y/N):	No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83008 001100	30 MT	0.181 KG	BROWN		#20 STR TFE BRN
83008 0011000	305 MT	2.722 KG	BROWN	SW	#20 STR TFE BRN

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83008 Hook-up/Lead - UL AWM Style 1213

83008 002100	30 MT	0.181 KG	RED		#20 STR TFE RED
83008 0021000	305 MT	2.722 KG	RED	SW	#20 STR TFE RED
83008 003100	30 MT	0.181 KG	ORANGE		#20 STR TFE ORG
83008 0031000	305 MT	2.722 KG	ORANGE	SW	#20 STR TFE ORG
83008 004100	30 MT	0.181 KG	YELLOW		#20 STR TFE YEL
83008 0041000	305 MT	2.722 KG	YELLOW	SW	#20 STR TFE YEL
83008 005100	30 MT	0.181 KG	GREEN, DARK		#20 STR TFE GRNDK
83008 0051000	305 MT	2.722 KG	GREEN, DARK	SW	#20 STR TFE GRNDK
83008 006100	30 MT	0.181 KG	BLUE, LIGHT		#20 STR TFE BLULT
83008 0061000	305 MT	2.722 KG	BLUE, LIGHT	SW	#20 STR TFE BLULT
83008 0071000	305 MT	2.722 KG	VIOLET	SW	#20 STR TFE VIO
83008 009100	30 MT	0.181 KG	WHITE		#20 STR TFE WHT
83008 0091000	305 MT	2.722 KG	WHITE	SW	#20 STR TFE WHT
83008 010100	30 MT	0.181 KG	BLACK		#20 STR TFE BLK
83008 0101000	305 MT	2.722 KG	BLACK	SW	#20 STR TFE BLK

Notes:

S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER10 W = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 75'

Revision Number: 2 Revision Date: 07-10-2012

© 2013 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implication of warding research and a statutory or implication of warding statutory or implication of the statutory or implication of the statutory of t negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU ROHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.