Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



83028 Hook-up/Lead - UL AWM Style 1180

For more Information please call

1-800-Belden1



General Description:

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

Physical Characteristics (Overall)

Conducto

AWG:

# Conductors	AWG	Stranding	Conductor Material			
1	20	7x28	SPC - Silver Plated Copper			

Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)			
TFE - Tetrafluoroethylene	.015			

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.068 in.

Mechanical Characteristics (Overall)

Bulk Cable Weight: 6.900 lbs/1000 ft.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

	UL AWM Style:	1180
	UL Rating:	300 V RMS, 200°C
	EU Directive 2011/65/EU (ROHS II):	Yes
	Other Standards:	MIL-W-16878/5
	EU CE Mark:	Yes
	EU Directive 2000/53/EC (ELV):	Yes
	EU Directive 2002/95/EC (RoHS):	Yes
	EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
	EU Directive 2002/96/EC (WEEE):	Yes
	EU Directive 2003/11/EC (BFR):	Yes
	CA Prop 65 (CJ for Wire & Cable):	Yes
	MII Order #39 (China RoHS):	Yes
	Military Specification:	1000 V, 200°C
Flame Test		
	UL Flame Test:	VW-1
Ple	num/Non-Plenum	
	Plenum (Y/N):	No

Electrical Characteristics (Overall)

Max. Recommended Current:

Description	Current
Mil-Std-975M Table 3.16 (Single wire)	6.5 amps

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83028 002100	100 FT	0.600 LB	RED		#20 STR TFE RED
83028 0021000	1,000 FT	7.000 LB	RED	SW	#20 STR TFE RED

Page 1 of 2 10-17-2016

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



83028 Hook-up/Lead - UL AWM Style 1180

83028 003100	100 FT	0.600 LB	ORANGE		#20 STR TFE ORG
83028 0031000	1,000 FT	7.000 LB	ORANGE	SW	#20 STR TFE ORG
83028 005100	100 FT	0.600 LB	GREEN, DARK		#20 STR TFE GRNDK
83028 0051000	1,000 FT	7.000 LB	GREEN, DARK	SW	#20 STR TFE GRNDK
83028 006100	100 FT	0.600 LB	BLUE, LIGHT		#20 STR TFE BLULT
83028 0061000	1,000 FT	7.000 LB	BLUE, LIGHT	SW	#20 STR TFE BLULT
83028 009100	100 FT	0.600 LB	WHITE		#20 STR TFE WHT
83028 0091000	1,000 FT	7.000 LB	WHITE	SW	#20 STR TFE WHT
83028 010100	100 FT	0.600 LB	BLACK		#20 STR TFE BLK
83028 0101000	1,000 FT	7.000 LB	BLACK	SW	#20 STR TFE BLK

S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER10 W = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 75'

Revision Number: 1 Revision Date: 10-03-2016

© 2016 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sales.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2