Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



83303E Multi-Conductor - MIL-W-16878/4 (Type E)

For more Information please call

1-800-Belden1



General Description:

26 AWG stranded (7x34) silver-plated copper conductors, cabled and color-coded, extruded TFE Teflon® insulation, silver plated copper braid shield (85% coverage), TFE teflon tape-wrapped jacket.

Physical Characteristics (Overall)	
Conductor AWG:	
#Conductors AWG Stranding Conductor Material	
1 26 7x34 SPC - Silver Plated Copper	
Total Number of Conductors:	1
Insulation	
Insulation Material: Insulation Trade Name Insulation Material Wall Thickness (i	in \
Teflon® TFE - Tetrafluoroethylene .010	
Insulation Resistance:	100,000 Megaohms/1000 ft. @ 500 V DC
Outer Shield Outer Shield Material:	
Type Outer Shield Material Coverage (%) Braid SPC - Silver Plated Copper 85	
Outer Jacket Outer Jacket Material:	
Outer Jacket Trade Name Outer Jacket Material Nom. Wall Thi Teflon® TFE - Tetrafluoroethylene .010	ckness (in.)
Overall Cable Overall Cabling Color Code Chart: Color	
White Overall Nominal Diameter:	0.076 in.
Marshautan Ohanatailatta (Oassell)	
Mechanical Characteristics (Overall)	-65°C To +200°C
Operating Temperature Range:	
Bulk Cable Weight:	6 lbs/1000 ft.
Max. Recommended Pulling Tension:	13.100 lbs.
Min. Bend Radius/Minor Axis:	1 in.
Applicable Specifications and Agency Compliance (Ov	verall)
Applicable Standards & Environmental Programs	
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-W-16878/4 (Type E insulated conductors)
	100

Page 1 of 2 08-26-2016

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



83303E Multi-Conductor - MIL-W-16878/4 (Type E)

Plenum/Non-Plenum			
Plenum (Y/N):	No		
Electrical Characteristics (Overall)			
Nom. Capacitance Conductor to Shield:			

Capacitance (pF/ft)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

Max. Operating Voltage - UL:

Voltage 600 V RMS

Max. Recommended Current:

Current 3 Amps per conductor @ 25°C

Notes (Overall)

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83303E 0091000	1,000 FT	7.000 LB	WHITE	E	1 #26 TFE BRD TFE TAPE
83303E 009500	500 FT	3.500 LB	WHITE	E	1 #26 TFE BRD TFE TAPE

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Date: 09-04-2012 Revision Number: 5

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Page 2 of 2