



# Product: <u>8780</u> ☑

# Audio Cable, #16-1pr, TC, O/A Shield, CMG

## **Product Description**

16 AWG stranded (19x29) tinned copper conductors, PVC insulation, twisted pair, tinned copper spiral wrapped shield (85% coverage), PVC jacket.

## **Technical Specifications**

## **Product Overview**

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v,); low voltage digital control (24v,); line level audio; computer communication; panel wiring	

### **Physical Characteristics (Overall)**

Conductor	
-----------	--

AWG	Stranding	Material	Nomina	l Diameter	No. of Pairs
16	19x29	TC - Tinned Copper	0.059 in		1
Conductor Count: 2					
Total Number of Pairs:		1			

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.105 in	0.023 in

#### Color Chart

Color

Black and White

#### Outer Shield

Туре	Material	Coverage [%]
Spiral Serve / Screen	Tinned Copper (TC)	85%

#### Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.28 in	0.030 in

#### **Electrical Characteristics**

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCF
4.75 Ohm/1000ft	4.75 Ohm/1000ft	19 Ohm/1000ft

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
57 pF/ft	98 pF/ft

## Inductance

Nominal Inductan
0.18 µH/ft

#### Impedance

Nominal Characteristic Impedance

#### Delay

Nominal Velocity of Propagation (VP) [%] 65%

## Current

Max. Recommended Current [A]

7.1 Amps per Conductor at 25°C

### Voltage

UL Voltage Rating 300 V RMS

## **Temperature Range**

UL Temp Rating:	0°C
Operating Temperature Range:	-20°C To +60°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	42 lbs/1000ft
Max. Pull Tension:	61 lbs
Min. Bend Radius/Minor Axis:	3 in

## **Standards**

NEC/(UL) Compliance:	CMG
CEC/C(UL) Compliance:	CMG

## Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:

## Flammability, LS0H, Toxicity Testing

Yes

No

C(UL) Flammability:	FT4
IEEE Flammability:	1202
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum	(V/N)	۱.
Fienum	(1/14)	

#### **Related Part Numbers**

#### Variants

Item #	Color	Put-Up Type	Length	UPC
8780 060500	Chrome	Reel	500 ft	612825216322
8780 0601000	Chrome	Reel	1,000 ft	612825216315
8780 060U1000	Chrome	UnReel	1,000 ft	612825216339
8780 0605000	Chrome	Reel	5,000 ft	612825216292
Footnote:			C - CRATE REEL	

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.