

Product: <u>88241</u> ☑

Analog Video, RG59, #23 Solid BCCS, 95% BC Braid, FEP Jacket, CMP



Product Description

23 AWG Solid .023" bare copper-covered steel conductor, plenum, FEP insulation, bare copper braid shield (95% coverage), FEP jacket.

Technical Specifications

Physical Characteristics (Overall) Conductor AWG Stranding Nominal Diameter No. of Coax 23 Solid BCCS - Bare Copper Covered Steel 0.023 in Conductor Count: Insulation Nominal Diameter FEP - Fluorinated Ethylene Propylene 0.132 in **Outer Shield** Material Braid Bare Copper (BC) 95% **Outer Jacket Nominal Diameter** FEP - Fluorinated Ethylene Propylene 0.19 in **Electrical Characteristics** Conductor DCR Nominal Conductor DCR Nominal Conductor DCR Conductor Resistance | Nominal Outer Shield DCR Outer Conductor DCR 49 Ohm/1000ft 49 Ohm/1000ft 2.6 Ohm/1000ft 2.6 Ohm/1000ft Capacitance Nom. Capacitance Conductor to Shield 19.5 pF/ft

Inductance

Nominal Inductance

Impedance

Nominal Characteristic Impedance
75 Ohm

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 1 MHz | 0.5 dB/100ft |
| 10 MHz | 1 dB/100ft |
| 50 MHz | 2.3 dB/100ft |

| 100 MHz | 3.3 dB/100ft |
|----------|---------------|
| 200 MHz | 5.2 dB/100ft |
| 400 MHz | 8.4 dB/100ft |
| 700 MHz | 11.6 dB/100ft |
| 900 MHz | 13.8 dB/100ft |
| 1000 MHz | 14.8 dB/100ft |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.45 ns/ft | 70% |

Voltage

| Non-UL Voltage Rating | UL Voltage Rating |
|-----------------------|-------------------|
| 1700 V RMS | 300 V RMS |

Temperature Range

| Non-UL Temp Rating: | 200°C |
|------------------------------|-----------------|
| Operating Temperature Range: | -70°C To +200°C |

Mechanical Characteristics

| Bulk Cable Weight: | 36 lbs/1000ft |
|------------------------------|---------------|
| Max. Pull Tension: | 62 lbs |
| Min. Bend Radius/Minor Axis: | 2.5 in |

Standards

| NEC/(UL) Compliance: | СМР |
|-----------------------|-----|
| CEC/C(UL) Compliance: | CMP |
| CPR Euroclass: | Eca |
| RG Type: | 59 |

Applicable Environmental and Other Programs

| Environmental Space: | Indoor/Outdoor |
|--|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| EU Directive 2011/65/EU (RoHS 2): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU (RoHS 2 amendment): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | No |
| MII Order #39 (China RoHS): | Yes |

Suitability

| Suitability - Burial: | Yes |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |

Flammability, LS0H, Toxicity Testing

| UL Flammability: | NFPA 262 |
|--------------------|---------------|
| CSA Flammability: | FT6 |
| IEC Flammability: | IEC 60332-1-2 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| 1 | Plenum (Y/N): | Yes |
|---|---------------|-----|
| | | |

Related Part Numbers

| Non-Plenum Number: | 8241 |
|--------------------|------|

Variants

| | | | 612825216957 |
|-----------------------|------|----------|--------------|
| 88241 0101000 Black F | Reel | 1,000 ft | 612825216933 |

Footnote:

C - CRATE REEL PUT-UP.

History

| Update and Revision: | Revision Number: 0.348 Revision Date: 04-08-2022 |
|----------------------|--|

© 2022 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.