



Product: [8890](#)

Lead Wire, #24 Str TC, EPDM Ins

[Request Sample](#)

Product Description

Low Temp Rubber Lead Wire, 24AWG (45x40) Tinned Copper, EPDM Insulation, 1000V 90C

Technical Specifications

Product Overview

Suitable Applications:	used as test probe lead for electrical and electronic measuring for test equipment
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
24	45x40	TC - Tinned Copper	1

Conductor Count:	1
------------------	---

Insulation

Material	Nominal Wall Thickness
EPDM - Ethylene Propylene Diene Monomer	0.019 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
24.2 Ohm/1000ft

Voltage

Breakdown Voltage	Non-UL Voltage Rating	Suggested Working Voltage
10,000 V	1000 V	1,000 V

Temperature Range

Non-UL Temp Rating:	90°C
---------------------	------

Mechanical Characteristics

Bulk Cable Weight:	3.3 lbs/1000ft
Min Bend Radius/Minor Axis:	0.66 in

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

CA Prop 65:	Yes
MIL Order #39 (China RoHS):	Yes

Flammability, LSOH, Toxicity Testing

UL voltage rating:	N/A
--------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
8890 010100	Black	Reel	100 ft	612825217534
8890 010500	Black	Reel	500 ft	612825217541
8890 002100	Red	Reel	100 ft	612825217510
8890 002500	Red	Reel	500 ft	612825217527

Product Notes

Notes:	10000 V Breakdown
--------	-------------------

History

Update and Revision:	Revision Number: 0.298 Revision Date: 07-26-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.